View NSN Online: https://aerobasegroup.com/nsn/8030-00-926-2133

Product ID:FILLER, DENT MSDS Date:06/01/1987 FSC:8010 NIIN:00-926-2133 Kit Part:Y MSDS Number: BFWTQ === Responsible Party === Company Name: DETROIT BODY FILLER INC. Address:4700 - 13TH STREET City:WYANDOTTE State:MI ZIP:48192 Country:US Info Phone Num:313-285-1480 Emergency Phone Num:313-285-1480 CAGE: DETRO === Contractor Identification === Company Name: DETROIT BODY FILLER INC. Address:4700 - 13TH STREET Box:City:WYANDOTTE State:MI ZIP:48192 Country:US Phone:313-285-1480 CAGE:DETRO Ingred Name: BENZOYL PEROXIDE (WET WITH WATER) CAS:94-36-0 RTECS #:DM8578000 Fraction by Wt: 48-52% Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acu

te and Chronic:CAUSES SKIN AND EYE IRRITATION. MAY CAUSE DROWSINESS. IF INGESTED CAN CAUSE NAUSEA, GASTROINTENSTINAL IRRITATION, VOMITING, DIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS.PROLONGED INH ALATION OF VAPORS MAY CAUSE LUNG DAMAGE.
Effects of Overexposure:NONE Medical Cond Aggravated by Exposure:NONE
======================================
First Aid:EYES-IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEE A PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. INHALATION-REMOVE TO FRESH AIR.INGESTION-DO NOT INDUCE VOMITING. SEE A P HYSICIAN.
======================================
Flash Point:80F - 27C Extinguishing Media:WATER FROM A SAFE DISTANCE Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPPED WITH FLAME RESISTANT CLOTHING, HELMETS AND SELF CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:IN CASE OF FIRE NEAR STORAGE AREA, COOL
THE CONTAINER OF CREAM HARDENER WITH WATER SPRAY.
======================================
Spill Release Procedures:WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSING.
======================================
Handling and Storage Precautions:AVOID TEMPERATURES OF OVER 100F IN STORAGE. Other Precautions:NONE
======================================
Pospiratory Protoctio

Respiratory Protectio

n:100 PPM AND ABOVE, USE SELF CONTAINER APPARATUS (FOR STYRENE)
Ventilation:LOCAL EXHAUST SHOULD BE SUFFICIENT. MECHANICAL (GENERAL) COULD BE USEFUL.
Protective Gloves:NONE NEEDED
Eye Protection:WEAR GOGGLES
Other Protective Equipment:NONE NEEDED
Work Hygienic Practices:NORMAL WORK CLOTHES
Supplemental Safety and Health
PART "B" OF TWO PART PRODUCT. SEE P/N INDICATOR A FOR PART "A".

Spec Gravity:1.1-1.2 Evaporation Ra te & Reference:NONE Solubility in Water:NEGLIGIBLE Appearance and Odor:HEAVY PASTE WIT SLIGHT ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS Conditions to Avoid Polymerization:OPEN FLAMES, LONG EXPOSURE TO INTENSE SUNLIGHT

====== Disposa

Waste Disposal Methods: INCINERATE IN AN APPROVED INCINERATOR OR DISPOSE OF IN A CHEMICAL DUMP IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabili

ty for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.