

FLTRON CO INC -- FA4498 -- 5915-00-952-3046

=====  
Product Identification  
=====

Product ID:FA4498  
MSDS Date:01/01/1985  
FSC:5915  
NIIN:00-952-3046  
MSDS Number: BFYYG  
=== Responsible Party ===  
Company Name:FLTRON CO INC  
Address:148 SWEET HOLLOW RD  
City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
Emergency Phone Num:914-699-2000  
CAGE:MO356

==== Contractor Identification ====  
Company Name:FILTRON C  
O INC  
Address:148 SWEET HOLLOW RD  
Box:City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
Phone:914-699-2000  
CAGE:81831  
Company Name:FLTRON CO INC  
Address:148 SWEET HOLLOW RD  
Box:City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
CAGE:MO356

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)  
CAS:1336-36-3  
RTECS #:TQ1350000  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
Hazards Identification  
=====

=====

Effects of Overexposure:INHAL:RESP TK IRRIT;  
SKIN/EYE;IRRIT,INFLAM,CHLROACNE; MAY CAUSE LIVER DAMAGE

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR, IF BRTHNG  
DIFF,GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH  
W/SOAP&WATER. RMV CONTAM CLTHNG&SHOES. INGEST:INDUCE VOMIT. RPT  
UNTIL VOMIT IS CLEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD  
BRTHG APP.  
Unusual Fire/Explosion Hazard:MATL IS NON-FLAMMABLE BUT MAY GENERATE  
TOXIC GASES IN HEAT OF FIRE

===== Accidental Release Measures =====

Spill Release Procedures:EVAC NON-ESSENTL PERSONNEL. VENT SPIL AREA.  
WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON  
-REACTIVE MATL  
(SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING OR OTHER SUITABLE MEANS.  
CLEAN AREA W/SUITABLE SAFETY SOLVENT. LAUNDER CONTAMINATED  
CLOTHING.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED  
Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND  
PLASTIC. DO NOT USE CO  
NTAMINATED WORK CLOTHING. WASH/SHOWER AFTER  
EXPOSURE TO PCB'S.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.  
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES/FACE SHIELD  
Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING.  
Supplemental Safety and Health  
OVEREXPOS:CAN CAUSE FORMATION OF CYSTS.CAUSES STILLBIRTHS.IRRITATES  
EYES,NOSE,THROAT.

=====

===== Physical/Chemical Properties =====

HCC:Z3

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PALE YELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:SEE OTHER PRECAUTIONS

Hazardous Decomposition Products:HYDROGEN CHLORIDE, CO, & OTHER  
TOXIC/IRRITATING GASES/FUMES.

===== Disposal Considerations ==

=====

Waste Disposal Methods:CONTROLLED DISPOSAL REQD. GEN. V.HIGH TEMP  
INCINERATION. IAW ALL LOCAL, STATE, FEDERAL & REGULATIONS.  
PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.