View NSN Online: https://aerobasegroup.co.il/nsn/8010-00-965-2390

ILLINOIS BRONZE PAINT CO -- LACQUER SPRAY PAINT -- 8010-00-965-2390

Product ID:LACQUER SPRAY PAINT MSDS Date:01/01/1987 FSC:8010 NIIN:00-965-2390 **MSDS Number: BFZRN** === Responsible Party === Company Name: ILLINOIS BRONZE PAINT CO Address:300 EAST MAIN STREET City:LAKE ZURICH State:IL ZIP:60047-2580 Country:US Info Phone Num:312-488-8001 **Emergency Phone Num:800-**228-5635 CAGE:91794 === Contractor Identification === Company Name: ILLINOIS BRONZE PAINT COMPANY Address:300 EAST MAIN STREET **City:LAKE ZURICH** State:IL ZIP:60047-2580 Country:US Phone:800-228-5635 CAGE:91794

Ingred Name:MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 10% ACGIH TLV:500 PPM

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 13% OSHA PEL:100 PPM

I

ngred Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III) CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 29.0% Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM; Z-2
ACGIH TLV:50 PPM, A2; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ingred Name:ISOBUTANE-PROPANE (50-50 MOL WT%) Fraction by Wt: 33.0%
======================================
Effects of Overexposure:INHAL:ANEST:IRRIT OF RESPIRAT TRACT OR ACUT NERV SYS DEPRESSION,HDACH,DIZZ,STAG GAIT,UNCONSCON, COMA
======================================
First Aid:FUMES:REMOV FR EXPOS.GET FRESH AIR.SPRAY(EYES)FLUSH IMMED.W/LG QTY OF RUNNING WATER F/AT LEAST 15 MIN.TAKE TO A DR.SPRAY(SKIN):WIPE OFF W/TOWEL.REMOV REMAIN W/MINERAL SPIRITS,TURPENTINE OR LACQUER THI NNER,IN CASEOF LACQ.WASH W/SOAP & WATR.REMOV CONTA
======================================
Flash Point:-40 F-40 C
Extinguishing Media:USE NFPA CL B EXTING(CO*2,DRY CH EM OR FOAM)F/CLIA FLAMBL LIQ
Fire Fighting Procedures:WEAR GOGG & SELF CONTNEDBREATHING APPARAT.WATR SPRAY MAY(SUP
Unusual Fire/Explosion Hazard:CNS WILL RUPTR FRINTERNAL PRESSR AT ABOUT 190 F & DSCHRG FLAMBL CONTENTS.TOXIC FUMES IF HTD TO DECOM
======================================
Spill Release Procedures: REMOV ALL SOURCES OF IGNIT (FLAMES, HOT

SURFACES & ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOV W/INE

## RT ABSORBENT.

Handling and Storage Precautions:DO NOT STORE ABOVE 120 F.STORE LG QUANTITIES IN BLDGS DESIGNED & PROTECTED F/STORAGE OF NFPA CLASS IA FLAMMABLE LIQUIDS.

Other Precautions:DO NOT SPRAY IN EYES.DO NOT PUNCT OR INCINER CNS.DO NOT STICK PIN,NAIL OR ANY OTHR SHARP OBJECTS INTO OPEN ON TOP OF CN.DO NOT TAKE INTERN.AVD BREATHING OF VAP OR SPRAY MIST.DO NOT FLAME(SUPP)

====== Exposure Contro Is/Personal Protection ==========

Respiratory Protection:CASUAL USE,NONE REQD,IF VENTILAT IS AVAIL AS OUTLINED BELOW.
Ventilation:DILUTION OR EXHAUST TO KEEP BELOW TLV.
Protective Gloves:NONE
Eye Protection:NO SPEC PROTECTION REQD.
Supplemental Safety and Health
SPEC. FIRE FIGHT:BE INEFFECT,WATR MAY BE USED TO COOL CLOSED CONTNR TO PRUNT PRESSR BUILD-UP & EXPLOSION WHEN EXPOS TO EXTREM HEAT. OTH PRECAUT:CUT,BRAZE OR WELD W/O U.S BUR OF MNES APPRV RESP

====== Physic

HCC:V3 Boiling Pt:B.P. Text:42-391 F Vapor Density:HEAV Evaporation Rate & amp; Reference:PROPELLANT-FASTER Percent Volatiles by Volume:88

Stability Indicator/Materials to Avoid:YES

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL,STATE & FEDERAL REGULATIONS. INCINERATE IN APPRVD FACILITY.DO NOT INCINERAT

## E CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.