View NSN Online: https://aerobasegroup.com/nsn/6810-00-985-7098

N/P -- METHYL ETHYL KETONE -- 6810-00-985-7098 Product ID:METHYL ETHYL KETONE MSDS Date:01/01/1985 FSC:6810 NIIN:00-985-7098 MSDS Number: BGBRG === Responsible Party === Address:186 LINCOLN ST SUITE 502 City:BOSTON State:MA ZIP:02111-2403 Country:US **Emergency Phone Num:NONE** CAGE:86511 === Contractor Identification === Company Name: PHIPPS PRODUCTS CORP Address:186 LINCOLN ST SUITE 502 Box:City:BOSTON State:MA ZIP:02111-2403 Country :US Phone:OUT OF BUSINESS CAGE:86511

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Effects of Overexposure: IRRITATION OF EYES, NASAL PASSAGES & CORNEAL EDEMA. HEADACHE, NAUSEA, NARCOSIS AT LEVELS OF 10000 PPM

First Aid: EYES-WASH THOROUGHLY WITH WATER. SKIN-WASH WITH SOAP &

WATER.REMOVE CONTAMINATED CLOTHING.REMOVE TO FRESH AIR.GIVE ARTIFICIAL RESPIRATION & OXYGEN IF NECESSARY.IF SWALLOWED,INDUCE VOMITING & CALL A PHY SICIAN

Flash Point:21F TCC Lower Limits:1.8 Upper Limits:10.0 Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,ALCOHOL TYPE FOAM Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS IN CONFINED AREAS Unusual Fire/Explosion Hazard:SERIOUS FIRE HAZARD BECAUSE OF LOW FLASH

POINT, HIGH VOLATILITY & HEAVY VAPOR

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES FLUSH SPILL WITH LARGE VOLUMES OF WATER. DIKE LARGE SPILLS & DUMP TO SALVAGE TANKS OR ABSORB.NOTIFY AUTHORITIES IN THE EVENT OF LARGE SPILLS

Handling and Storage Precautions:KEEP FROM HEAT,SPARKS,& OPEN FLAME.AVOID PROLONGED BREATHING OF VA PORS.AVOID SKIN CONTACT Other Precautions:ALSO INCOMPATIBLE WITH CAUSTICS,INORGANIC ACIDS,ISOCYANATES,COPPER(POSSIBLE PRESENCE OF ACETYLENE)

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS OR ORGANIC CHEMICAL CANISTERS Ventilation:LOCAL-PREFERABLE Protective Gloves:RUBBER Eye Protection:CHEMICAL SAFETY GOGGLES Other Protective Equipment:IMPERVIOUS APRON & BOOTS,EYE BATH & SAFETY SHOWER Supplemental Safety and Health ITEM COMPOSITION IS IN PERCENT BY VOLUME

HCC:F2 Boiling Pt:=79.6C, 175.1F Vapor Pres:71 Vapor Density:2.5 Spec Gravity:0.806 Evaporation Rate & amp; Reference:5.7%-BUTYL ACETATE Solubility in Water:27.1 Appearance and Odor:COLORLESS LIQUID,ACETONE-LIKE ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES ALCOHOL,AMINES, PYRIDINES,AMMONIA,SEE OTHER PRECAUTION SECT Stability Condition to Avoid:HEAT,SPARK,OPEN FLAME Hazardous Decomposition Products:NONE

Waste Disposal Methods:PLACE ABSORBED MATERIAL IN DRUMS SUITABLE FOR SHIPPING TO DISPOSAL AREA.LARGE QUANTITIES SHOULD NOT BE PERMITTED TO ENTER DRAINS WHERE THERE IS DANGER OF VAPORS IGNITING

Disclaimer (provided with this information by the compiling agencies): This information is fo

rmulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.