

VARFLEX CORPORATION -- SYNTHOLVAR 120/210 -- 5970-00-997-6347

===== Product Identification =====

Product ID:SYNTHOLVAR 120/210

MSDS Date:10/01/1985

FSC:5970

NIIN:00-997-6347

MSDS Number: BGCLM

=== Responsible Party ===

Company Name:VARFLEX CORPORATION

Address:512 WEST COURT STREET

City:ROME

State:NY

ZIP:13440

Country:US

Info Phone Num:315-336-4400

Emergency Phone Num:315-336-4400

CAGE:79074

===

Contractor Identification ===

Company Name:VARFLEX CORPORATION

Address:512 WEST COURT STREET

Box:City:ROME

State:NY

ZIP:13440

Country:US

Phone:315-336-4400

CAGE:79074

===== Composition/Information on Ingredients =====

Ingred Name:PLASTICIZED POLYVINYL CHLORIDE RESIN

Ingred Name:ADDITIVES (INCLUDES 5% PIGMENTS)

CAS:24937-78-8

Fraction by Wt: 5.5%

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: NONE SPECIFIED BY MANUFACTURER.
CHRONIC: NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:MATERIAL IS NOT CONSIDERED AS A
CARCINOGEN BY NTP, IARC OR OSHA
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:IF VAPORS FROM HIGH TEMPERATURES
ARE INHALED, REMOVE TO FRESH
AIR.

=====
Fire Fighting Measures
=====

Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:WATER
Fire Fighting Procedures:NO SPECIAL REQUIREMENTS.
Unusual Fire/Explosion Hazard:HYDROGEN CHLORIDE GAS LIBERATED DURING
COMBUSTION AND AT 500F AND ABOVE.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT EXPOSE TO SUNLIGHT. STORE BELOW
70 DEG. F.
Other
Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED.
Ventilation:MECHANICAL(GENERAL) RECOMMENDED.
Protective Gloves:NONE
Eye Protection:NONE
Other Protective Equipment:NONE
Work Hygienic Practices:WASH AND SHOWER NORMALLY AT THE END OF A
WORKDAY.
Supplemental Safety and Health
NONE

=====
Physical/Chemical Properties
=====

HCC:N1
Decomp Temp:Decomp Text:>500F,>260C
Spec Gravity:1.19-1.41
So

lubility in Water:INS.

Appearance and Odor:CLEAR PLASTIC INSULATION SLEEVING, 100 FOOT SPOOL.
NO ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

DIRECT CONTACT WITH SILVER AND COPPER UNDER CERTAIN CONDITIONS CAN
CAUSE CORROSION.

Stability Condition to Avoid:TEMPERATURES OVER 400F.

Hazardous Decomposition Products:HYDROGEN CHLORIDE GAS IS LIBERATED
DURING COMBUSTION AND AT 500F OR HIGH
ER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW LOCAL,STATE,FED.REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek
competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.