

BEL-RAY COMPANY,INC -- MOLYLUBE SILICONE LH-10 GREASE -- 9150-01-019-0669

===== Product Identification =====

Product ID:MOLYLUBE SILICONE LH-10 GREASE

MSDS Date:01/01/1985

FSC:9150

NIIN:01-019-0669

MSDS Number: BGDWY

=== Responsible Party ===

Company Name:BEL-RAY COMPANY,INC

Emergency Phone Num:201-938-2421

CAGE:KO301

=== Contractor Identification ===

Company Name:BEL-RAY COMPANY INC.

Address:1

201 BOWMAN AVE

Box:526

City:FARMINGDALE

State:NJ

ZIP:07727

Country:US

Phone:732-938-2421

CAGE:12474

Company Name:BEL-RAY COMPANY,INC.

Box:526

CAGE:KO301

===== Composition/Information on Ingredients =====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 10.0%

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:SILICA

Fraction by Wt: 7.0%

ACGIH TLV:30 MG(DUST)/CUM

Ingred Name:SOLIDS, HAZARD UNKNOWN,UNIDENTIFIED; % WT BY DIFFE

RENCE
Fraction by Wt: 83.0%

===== Hazards Identification =====

Effects of Overexposure:MFR STATES THAT NO KNOWN ADVERSE EFFECTS FROM EXPOSURE

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

===== Fire Fighting Measures =====

Flash Point:530F-COC
Lower Limits:1.0%
Upper Limits:6.0%
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:FOR ENCLOSED AREAS USE AIR SUPPLIED RESCUE EQUIPMENT
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:USE PROTECTV GLOVES FOR CLEAN-UP; WIPE,CONTAIN & RECOVER.PLACE IN COVERED CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:NORMAL ROOM VENTILATION.
Protective Gloves:AS REQUIRED
Eye Protection:AS REQUIRED
Other Protective Equipment:USE GOOD INDUSTRIAL HYGIENIC PRACTICES.
Supplemental Safety and Health
MSDS FM MFR DATED:11-30-81

===== Physical/Chemical

Properties =====

HCC:V6

Boiling Pt:B.P. Text:IBP >600F

Vapor Pres: .02

Vapor Density:>10

Spec Gravity:1.2

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREASE.

Percent Volatiles by Volume:1.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS SUCH AS CONCENTRATED OXYGEN/CHLORINE

Hazardous Decomposition Products:CO,CO*2 & SULFUR COMPOUNDS.

===== Disposal Considerations =====

=====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS. MFR NOTES:REMOVE
TO LANDFILL OR USE LICENS D WASTE OIL DISPOSAL CONTR.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warra

nts this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.