

EASTMAN KODAK COMPANY -- 183 2492,COLR DEVL REPL,E-6AR,PT A(PRE 5/84 --  
6750-01-034-1017

===== Product Identification =====

Product ID:183 2492,COLR DEVL REPL,E-6AR,PT A(PRE 5/84

MSDS Date:01/10/1983

FSC:6750

NIIN:01-034-1017

Kit Part:Y

MSDS Number: BGGGW

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone

Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 70-80%

Ingred Name:POTASSIUM PHOSPHATE,TRIBASIC

CAS:7778-53-2

Fraction by Wt: 10-15%

I

Ingredient Name: POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS #: TT2100000

Fraction by Wt: 1-5%

OSHA PEL: C, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure: EYES: CAUSES BURNS. SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE SKIN IRRITATION AND/OR BURNS.

=====  
First Aid Measures  
=====

First Aid: EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER AT LEAST 15 MIN. SKIN: IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR 15 MIN WHILE REMOVING CONTAMINATED CLOTHING. GET MEDICAL ATTENTION. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

=====  
Fire Fighting Measures  
=====

Flash Point: NONE  
Fire Fighting Procedures: NONE  
Unusual Fire/Explosion Hazard: NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures: WEAR SUITABLE PROTECTIVE CLOTHING. NEUTRALIZE WITH SODIUM BISULFATE. FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER. WASH CONTAMINATED AREA WELL WITH SOAP & WATER. FEDERAL, STATE AND LOCAL REGULATIONS TAKE PRECEDENCE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions: NO SPECIAL PRECAUTIONS. STORE IN COOL, DRY, LOW FIRE RISK AREA. KEEP CLOSED. PROTECT FROM PHYSICAL DAMAGE.  
Other Precautions: FORMULATION HAS NOT BEEN TESTED FOR ENVIRONMENTAL EFFECTS; IS A STRONG ALKALINE SOLUTION. IF FOR

MULATION DILUTED,NO  
ADVERSE ENVIRONMENTAL IMPACT WOULD BE EXPECTED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED  
Ventilation:MECHANICAL(GENERAL)RECOMMENDED LOCAL EXHAUST NONE NEEDED  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES:SIDE SHILD  
Other Protective Equipment:AS REQUIRED TO PREVENT REPEATED OR PROLONGED  
SKIN CONTACT  
Supplemental Safety and Health  
KEY1: B1. PART A OF THIS KIT IS NSN:6750-01-034-1017.P  
ART B OF THIS KIT  
IS NSN:6750-01-033-5154.

===== Physical/Chemical Properties =====

HCC:C1  
Boiling Pt:B.P. Text:>212F/100C  
Vapor Pres:17  
Vapor Density:0.6  
Spec Gravity:1.18  
pH:>13.0  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR,COLORLESS SOLUTION;ODORLESS.  
Percent Volatiles by Volume:78

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS  
Hazardous Decomposition Products:NONE

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WEAR SUITABLE PROTECTIVE EQUIPMENT.NEUTRALIZE  
WITH SODIUM BISULFATE.FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF  
WATER.WASH CONTAMINATED AREA WELL WITH SOAP & WATER.FEDERAL,STATE  
AND LOCAL EFFLUENT LAWS TAKE PECEDECENCE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of A

merica in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.