

EXXON COMPANY, U.S.A. -- WS 1311 GEAR OIL 80W-90 -- 9150-01-035-5392

=====
Product Identification
=====

Product ID:WS 1311 GEAR OIL 80W-90

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5392

MSDS Number: BGGJV

=== Responsible Party ===

Company Name:EXXON COMPANY, U.S.A.

Emergency Phone Num:713-656-3424

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON

Ingred Name:ADDITIVES

Ingred Name:PROPRIETARY COMPONENTS

Fraction by Wt: < 10% %

Other REC Limits:NONE RECOMMENDED

=====

==== Hazards Identification =====

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION.

==== First Aid Measures =====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WARM WATER.EYES: FLUSH WITH CLEAR WATER 15 MINS OR UNTIL IRRITATION SUBSIDES.

==== Fire Fighting Measures =====

Flash Point:450F,232C COC

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FO

AM,DRY CHEMICAL,WATER FOG OR SPRAY,OR CO*2.

Fire Fighting Procedures:AIR-SUPP BREATH EQUIP IN ENCLSD AREA. AVD BREATH VAPOR/FUMES

Unusual Fire/Explosion Hazard:COOL EXPSD CONT W/WATER SPRAY. DO NOT MIX OR STORE W/STRONG OXIDANTS LIKE LIQ CHLORINE OR CONC O*2

==== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID.ADD ABSORBENT(SAND,EARTH,SAWDUST,ETC)TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING.

ADVISE AUTHORITIES IF PRODUCT HAS OR MAY ENTER S EWERS, WATERCOURSES, OR EXTENSIVE LAND AREAS.

==== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.DO NOT HANDLE OR STORE NEAR HEAT,SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL-SMOKED CLOTHING AND LAUNDRER BEFORE RE-USE. DISCARD OIL-SOAKED SHOES. WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER HANDLING.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. SUPPLIED-AIR RESP IN CONFINED OR ENCLSD SPACES.

Ventilation:LOC EXHST. PROVIDE >60FPM HOOD/FACE VELOC IN CONFINED SPACES

Protective Gloves:CHEM RESISTANT

Eye Protection:SPLASH GOGGLE/FACE SHIELD

Other Protective Equipment:CHEM RESISTANT APRON TO AVOID PROLONGED SKIN CONTACT.

Supplemental Safety and Health

VP:0.01 ALL ENTRIES IN SECTION III(

PHYSICAL DATA) ARE APPROXIMATE.

PERCENT VOLATILE BY VOLUME: NEGLIGIBLE. CONTAINER SIZE:1 QT.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:650F,343C

Vapor Density:12.0

Spec Gravity:0.8900

Evaporation Rate & Reference:0.01,BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR,DARK AMBER LIQUID. MILD PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo

id:YES

STRONG OXIDANTS:LIQ CHLORINE, CONC O*2, NA, CA HYPOCHLORITE

Hazardous Decomposition Products:FUMES, SMOKE,CO, SOX, IN THE CASE OF INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED WASTE DISPOSAL SITE OR FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulat

ed for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.