

BRAY OIL CO., INC -- BRAYCO 689ALUBE OIL,GEAR,GR 80W/90 -- 9150-01-035-5393

=====
Product Identification
=====

Product ID:BRAYCO 689ALUBE OIL,GEAR,GR 80W/90

MSDS Date:01/01/1987

FSC:9150

NIIN:01-035-5393

MSDS Number: BGGLC

=== Responsible Party ===

Company Name:BRAY OIL CO., INC

Emergency Phone Num:714-850-1151

CAGE:LO548

=== Contractor Identification ===

Company Name:BRAY OIL CO., INC.

CAGE:LO54

8

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS
DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:800-621-2661/ FAX: 630-241-4140

CAGE:2R128

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON

Fraction by Wt: 91.6%

Ingred Name:ANLAMOL 99(TRADENAME CHEMICAL;SEE HMIS INDEX FOR DATA)

Fraction by Wt: 6.5%

Ingred Name:ACRYLOID 150(TRADENAME ADDITIVE;SEE HMIS INDES FOR DATA
)

Fraction by Wt: 2.0%

=====
Hazards Identification
=====

Effects of Overexposure:NOT EXPECTED TO CAUSE ILLEFFECT EXCEPT POSS IN
VERY SENSITIVE INDIVID; MAY CAUSE EYE IRRITATION.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH THOROUGHLY W/WATER;CALL MD. SKIN:WASH W/SOAP &
WATER. INGEST:DO NOT INDUCE VOMITING, CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:430F ASTM

D92-COC

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG

Fire Fighting Procedures: DO NOT USE WATER EXCEPT TO COOL CONTAINER OR TANK

Unusual Fire/Explosion Hazard: SELF-CNTND RESPIRATORY EQUIPMENT WHEN FIRE FIGHTING IN CONFINED AREA

===== Accidental Release Measures =====

Spill Release Procedures: STOP FLOW & SHUT OFF SOURCES OF IGNITION. WIPE OR MOP UP OR ABSORB WITH CLAY, DIATOMACEOUS EARTH, OR OTHER INERT MATERIAL. STORE IN CLOSED METAL CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE NEAR HEAT, OPEN FLAME OR OTHER SOURCES OF IGNITION.

Other Precautions: AVOID EYE CONTACT

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT NORMALLY REQUIRED EXCEPT IF OIL MIST EXCEEDS TLV.

Ventilation: ONLY IF OIL MIST EXCEEDS TLV

Protective Gloves: PLASTIC, RUBBER

Eye Protection: SAFETY GLASSES RECOMMENDED

Other Protective

Equipment: D

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: V6

Boiling Pt: B.P. Text: >500F

Spec Gravity: 0.907

Solubility in Water: INSOLUBLE

Appearance and Odor: DARK BROWN OILY LIQUID, PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID STRONG OXIDIZING MATERIALS

Hazardous Decomposition Products: COMBUSTION MAY PRODUCE CO & ASPHYXIANTS

=====

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED INCINERATION OR METHOD IN COMPLIANCE
W/LOCAL,STATE OR FEDERAL REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizin
g this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.