Product ID:BATTERY,LITHIUM MSDS Date:01/01/1985 FSC:6135 NIIN:01-036-3495 **MSDS Number: BGGRK** === Responsible Party === Company Name: DURACELL USA Address:60 ELM ST **City:TARRYTOWN** State:NY ZIP:10591-2222 Country:US Emergency Phone Num:914-631-4014 CAGE:DO224 === Contractor Identification === Company Name: DURACELL USA Address:305 NEW HIGHWAY 64 E City:LEXINGTON State:NC ZIP:27292 Phone:(617)449-7600 CAGE:DO224 Company Name: LITHIUM SYSTEMS DIVISION Address: DURACELL INTERNATIONAL INC Box:City:NORTH TARRYTOWN State:NY ZIP:10591 Country:US CAGE:4U371

Ingred Name:LITHIUM CAS:7439-93-2 RTECS #:OJ5540000 Fraction by Wt: 5.0%

Ingred Name:SULFUR DIOXIDE (SARA III) CAS:7446-09-5 RTECS #:WS4550000 Fraction by Wt: 30%. OSHA PEL:5 PPM/5 STEL ACG IH TLV:2 PPM/5 STEL; 9293

Ingred Name:ACETONITRILE (SARA III) CAS:75-05-8
RTECS #:AL7700000
Fraction by Wt: 10%. OSHA PEL:40PPM/60 STEL
ACGIH TLV:40PPM/60STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
======================================
Effects of Overexposure:NO EFFECTS IF SEAL AND CELL INTEGRITY IS MAINTAINED
======================================
First Aid:IF CELL IS OPENED,MAJOR EXPOSURE IS S02. PERSONNEL SHOULD B
EVACUATED FROM CONTAMINATED AREA AND ARTIFICIAL RESPIRATION STARTED IF BREATHING HAS CEASED. MEDICAL AID SHOULD BE SUMMONED.
======================================
Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:BATTERIES CAN VENT WHEN SUBJECTED TO EXCESSIVE HEAT, EXPOSING CELL CONTENTS.
======================================
Spill Release Procedures
:AVOID SKIN & EYE CONTACT. ON SKIN, SHOWER WITH WATER; ON EYE, WASH WITH WATER. SUMMON MEDICAL HELP.
======================================
Handling and Storage Precautions:SEE DURACELL BULLETIN 279
======================================
Supplemental Safety and Health
======================================
HCC:Z6
======================================
Stability Indicator/M

## aterials to Avoid:YES Stability Condition to Avoid:HEATING,VENTING,OPENING OR PUNCTURING CELL, ELECTRICAL ABUS

Waste Disposal Methods:SEALED CELL CAN BE DISPOSED OF IN SANITARY LANDFILLS.OPEN CELL SHOULD BE CAREFULLY DROWNED IN LARGE QUANTITIES OF WATER. OPERATOR SHOULD USE SAFETY EQUIPMENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.