

CARE LABORATORIES, INC. -- CARE 1910 -- 8030-01-045-4780

=====
Product Identification
=====

Product ID:CARE 1910

MSDS Date:01/01/1985

FSC:8030

NIIN:01-045-4780

MSDS Number: BGHLK

=== Responsible Party ===

Company Name:CARE LABORATORIES, INC.

Emergency Phone Num:215-279-3777

CAGE:58365

=== Contractor Identification ===

Company Name:CARE LABORATORIES INC

CAGE:58365

Company Name:GENERAL SERVICES ADM

INISTRATION FEDERAL SUPPLY SVC

Address:CRYSTAL MALL BLDG 4 1941 JEFFERSON DAVIS

Box:HWY

City:WASHINGTON

State:DC

ZIP:20406

Country:US

CAGE:80244

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICONE RESIN SOLUTION(45% TOLUENE,21% N-BUTANOL)

Fraction by Wt: 10.2%

ACGIH TLV:100PPM

Ingred Name:SILICONE ALKYD RESIN SOLUTION(10% TOLUENE)

Fraction by Wt: 30%

ACGIH TLV:100 PPM

Ingred Name:AROMATIC 150

Fraction by Wt: 21.2%

ACGIH TLV:100PPM

Ingred Name:ISOPROPYL A

LCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 4.6%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III)
CAS:76-13-1
RTECS #:KJ4000000
Fraction by Wt: 28.6%
OSHA PEL:1000PPM/1250STEL
ACGIH TLV:1000PPM/1250STEL9192
Ozone Depleting Chemical:1

=====
Hazards Identification
=====

Effects of Overexposure:AVOID BREATH VAPOR. INHALSATION:HIGH VAPOR CONC
RESULTS RAN
GING FROM DIZZ, HDCH TO UNCONSCIOUSNESS

=====
First Aid Measures
=====

First Aid:INHALATION:OVERCOME BY VAPOR REMOVE TO FRESH AIR. BREATH IS
IRREGULAR OR STOPPED, GIVE RESUSCITATION.ADMINISTER OXYGEN.CALL
PHYSICIAN. IF SWALLOWED DO NOT INDUCE VOMITING. EYES:FLUSH WITH
WATER AT LEA ST 15 MIN.

=====
Fire Fighting Measures
=====

Flash Point:147F TCC
Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER SPRAY,FOG
Fire
Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER
Unusual Fire/Explosion Hazard:DO NOT SOTRE OR MIX WITH STRONG OXIDANTS

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE PEOPLE FROM AREA AND ALL SOURCES OF
IGNITION. PROVIDE VENT. PREVENT LIQ FROM ENTERING SEWERS &
WATERWAYS. ADD ABSROBENT TO SPILL AREA. LARGE SPILLS MAY BE SCOOPED
UP WIT NONSPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS, OPEN FLAME. GROUND CONTAINERS WHEN POURING. USE WITH ADEQUATE VENT. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID BREATH VAPORS. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WASH SKIN WITH SOAP & WATER AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOS OF CONCERN.

Ventilation:LOCAL EXHAUST/EXHAUSTION PROOF MOTOR

Protective Gloves:CHEM RESISTANT

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:HYDROCARBON-INSOLUBLE APRON

Supplemental Safety and Health

ADDED INGRED:ALKYL AMMONIUM ORGANIC. PHOSPHATE. 1%,ANTHRAQUINENE DYE.1%

===== Physical/Chemical Properties =====

HCC:V4

Solubility in Water:NEGLIGIBLE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS. DISSOLVE OR SOFTEN SOME PLASTICS

Stability Condition to Avoid:HIGH TEMP,HEAT AND UVRADIATION

Hazardous Decomposition Products:INCOMP COMBUST:INCOMP COMBUST:CO,CO*2 & SIO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE BY SUPERVISED INCINERATION OR IN A CHEMICAL DISPOSAL AREA IN COMPLIANCE WITH STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by

elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.