View NSN Online: https://aerobasegroup.co.il/nsn/6850-01-067-6670

SIFCO SELECTIVE PLATING, DIV OF SIFCO INDUSTRIES -- 30101006 CLEANING & DEOXIDIZING SOLUTION -- 6850-01-067-6670

Product ID:30101006 CLEANING & DEOXIDIZING SOLUTION MSDS Date:04/17/1990 FSC:6850 NIIN:01-067-6670 MSDS Number: BGKDL === Responsible Party === Company Name: SIFCO SELECTIVE PLATING, DIV OF SIFCO INDUSTRIES Address:5708 SCHAFF ROAD City:CLEVELAND Sta te:OH ZIP:44131-1394 Country:US Info Phone Num:216-881-8600 Emergency Phone Num:216-881-8600 Preparer's Name: WERNER A EHRENSCHNEIDER CAGE:DO645 === Contractor Identification === Company Name: SIFCO SELECTIVE PLATING DIV OF SIFCO INDUSTRIES INC. Address: 5708 SCHAAF ROAD Box:City:CLEVELAND State:OH ZIP:44131-1394 Country:US Phone:216-524-0099/ FAX: -6331 CAGE:11924 Company Name: SIFCO SELECTIVE PLATING, DIV OF SIFCO INDUSTRIES INC Address:5708 SCHAAF ROAD City:CLEVELAND State:OH ZIP:44131-1394 Co untry:US Phone:216-524-0099 CAGE:DO645 Ingred Name:SODIUM HYDROXIDE (SARA III) CAS:1310-73-2 RTECS #:WB4900000 Fraction by Wt: 5% Other REC Limits:NOT SPECIFIED OSHA PEL:2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: UNIDENTIFIED COMPONENTS Ingred Name:WATER; CAS #7732-18-5 CAS:7732-18-5

RTECS #:ZC0110000

0 Mixture:TLV FOR SODIUM HYDROXIDE IS 2 MG/M3. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INHALE:BURNING NOSE & THROAT,SNEEZING,COUGHING,SEVERE IRRITATION,PULMONARY EDEMA.EYE:INTENSE IRRITATION,WATERING,BURNS,ULCERATION.MAY CAUSE LOSS OF EYES.SKIN:ITCHING,TINGLING,PAINFUL ULCERATION, SHOCK.ORAL:INTENSE BURNING SENSATION INMOUTH,THROAT,STOMACH,BLOODY DIARRHEA.DEATH POSSIBL

E.CHRONIC-DERMATITIS.

Effects of Overexposure:BURNING NOSE & THROAT, SNEEZING, COUGHING, SEVERE IRRITATION, PULMONARY EDEMA IF INHALED. INTENSE EYE IRRITATION, WATERING, BURNS, ULCERATION. MAY CAUSE LOSS OF EYES. ITCHING, TINGLING, PAINFUL ULCERA TION, SHOCK IF SKIN IS CONTACTED. ORALLYCAN CAUSE INTENSE BURNING SENSATION IN MOUTH, THROAT, STOMACH, BLOODY DIARRHEA.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

==

First Aid:GET MEDICAL ATTENTION IMMEDIATELY.EYE/SKIN:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES.HOLD EYELIDS OPEN.INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED.ORAL:DO NOT INDUCE VOMITING .IF CONSCIOUS,RINSE MOUTH & DRINK COLD WATER,MILK WITH 1-2 RAW EGGS,FRUIT JUICE,A GLASS OF 1/3 VINEGAR AND 2/3 WATER.CALL A PHYSICIAN IMMEDIATELY.NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERS

ON.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE. RUNOFF FROM FIRE CONTROL WATER MAY CAUSE POLLUTION. Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE CONTAINERS TO BURST. CONTACT WITH ALUMINUM, MAGNESIUM, TIN AND ZINC MAY GENERATE FLAMMABLE OR EXPLOSIVE HYDROGEN GAS.

Spill Release Procedures:WEAR PROPER EQUIPMENTS. VENTILATE AREA. ELIMINATE ALL SOURCES OF IGNITION (MAY FORM H2 GAS). STOP FLOW OF MATERIAL IF POSSIBLE. CAREFULLY MOP UP OR VACUUM SPILL AND TRIPLE RINSE WATER INTO A SUITABLE PLASTIC CONTAINER. DO NOT RELEASE INTO SOIL/SEWERS Neutralizing Agent:DILUTE HYDROCHLORIC ACID (6M)

Handling and Storage Precautions:STORAGE-STORE AT 50-90F AWAY FROM INCOMPATIBLE MATERIALS.SAFEGUARD CONTAINERS AGAINST SPILLAGE & MECHANICAL INJURY.

Other Precautions:DANGER! CAUSTIC. AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT OF REACH OF CH ILDREN.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MISTS. WEAR SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED OR ENCLOSED SPACES, IF NEEDED. Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves:NEOPRENE, VINYL, LATEX, NITRILE Eye Protection:SPLASH-PROOF CHEMICAL GOGGLES/FACESHIELD Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health

MFR DID NOT PROVIDE INGREDIENT # 2 AND 3. CLAIMED TRADE SECRET. INGREDIENTS OBTAINED FROM EARLIER MSDS.

HCC:B1 Boiling Pt:>100.C, 212.F Melt/Freeze Pt: