View NSN Online: https://aerobasegroup.co.il/nsn/6850-01-106-7671

TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC -- TRITON I ACTIVATOR SOLUTION

6850-01-106-7671

============= Product Identification =================

Product ID:TRITON I ACTIVATOR SOLUTION

MSDS Date:01/01/1987

FSC:6850

NIIN:01-106-7671

MSDS Number: BGMDJ === Responsible Party ===

Company Name: TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC

Address:331 N OAK ST

Box:398 City:OWEN State:WI ZIP:54460 Country:US

Emergency

Phone Num:201-647-1040

CAGE:MO933

=== Contractor Identification === Company Name:TELEDYNE INC Address:150 MT BETHEL ROAD

Box:City:WARREN

State:NJ

ZIP:07060-5147 Country:US CAGE:23428

Company Name: TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC

Address:331 N OAK ST

Box:398 City:OWEN State:WI ZIP:54460 Country:US CAGE:MO933

======= Composition/Information on Ingredients ========

Ingred Name: ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000 Fraction by Wt: UNK OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3

Ingred Name:DIPROPYLENE GLYCOL,1,1'-OXYDI-2-PROPANOL CAS:110-98-5 RTECS #:UB8785000 Fraction by Wt: UNK
======================================
Health Hazards Acute and Chronic:CONTACT WITH EYES CAUSES BURNS. SKIN CONTACT MAY CAUSE IRRITATION. BREATHING OF VAPORS MAY CAUSE COUGHING AND DISCOMFORT IN NOSE,THROAT AND CHEST. Medical Cond Aggravated by Exposure:MANUFACTURER DID NOT SPECIFY.
======================================
First Aid:IMMEDIATELY FLUSH SKIN & EYE CONTACT W/PLENTY OF WATER FOR AT LEAST 15 MINUTES.GET MEDICAL CARE FOR EYES.
======================================
Flash Point:200F/280F COC Lower Limits:5/1 Upper Limits:17/9 Extinguishing Media:CO*2 OR DRY CHEMICAL Fire Fighting Procedures:DILUTION OF BURNING LIQUID WITH WATER WILL REDUCE FLAME INT. Unusual Fire/Explosion Hazard:WIL BURN;MAY EXPLODE;RUN OFF MAY POLLUTE/CREATE EXPLOSV FIRE HAZ ARD.
========= Accidental Release Measures ===========
Spill Release Procedures:FLUSH WITH LARGE VOLUMES OF WATER.
======================================
Handling and Storage Precautions:WARNING:STRONG ALKALINE SOLUTION.HARMFUL IF SWALLOWED,AVOID CONTACT WITH EYES,SKIN,OR CLOTHING.IN CASE OF CONTACT WITH EYES OR SKIN FLUSH W/H*2O-15MIN Other Precautions:FOR EYES GET MEDICAL ATTENTION.
====== Exposure Controls/Personal Protection

PPM/6 STEL; 9192

=========

Respiratory Protection: NONE REQD.

Ventilation:LOCAL EXHAUST & MECHANICAL IS RECOMMENDED.

Protective Gloves:RUBBER Eye Protection:GOGGLES

Other Protective Equipment: EYE BATH & SAFETY SHOWER

Work Hygienic Practices: WASH HANDS THOROUGHLY BEFORE

EATING, SMOKING, USING SANITARY FACILITIES.

Supplemental Safety and Health

UPDATE PER UNDATED MSDS OSHA FORM 20 RECEIVED 8JAN88.

======== Physical/Chemical Properties ==========

HCC:N1 Boiling Pt:B.P. Text:339F/451 Va por Pres: