

WALTER KIDDE,DIV.OF KIDDE INC.,AEROSPACE OPERATION -- HALON 1301 -- 1680-01-135-6199
===== Product Identification =====

Product ID:HALON 1301

MSDS Date:01/01/1987

FSC:1680

NIIN:01-135-6199

MSDS Number: BGNKX

=== Responsible Party ===

Company Name:WALTER KIDDE,DIV.OF KIDDE INC.,AEROSPACE OPERATION

Address:2500 AIRPORT DRIVE

City:WILSON

State:NC

ZIP:27893-9604

Country:US

CAGE:NO024

=== Contractor I

dentification ===

Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

Box:City:WILSON

State:NC

ZIP:27893-9604

Country:US

Phone:252-237-7004

CAGE:61423

Company Name:WALTER KIDDE,DIV.OF KIDDE INC.,AEROSPACE OPERATION

Address:2500 AIRPORT DRIVE

Box:City:WILSON

State:NC

ZIP:27893-9604

Country:US

CAGE:NO024

===== Composition/Information on Ingredients =====

Ingred Name:TRIFLUOROBROMOMETHANE (HALON 1301) (SARA III)

CAS:75-63-8

RTECS #:PA5425000

Fract

ion by Wt: 96.2%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192
Ozone Depleting Chemical:1

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
Fraction by Wt: 3.8%
ACGIH TLV:ASPHYXIAN; 9192

=====
Hazards Identification
=====

Effects of Overexposure:LT HEAD,GIDD,DIZZ,SHORT OF BREATH.AT 10 VOL % &
HIGHER,NARCOSIS,CARDIAC ARRHYTHMIAS.

=====
First Aid Measures
=====

First Aid:REMOVE TO FRESH AIR.DO NOT GIVE EPINEPHRINE OR
SIMILAR
DRUGS.FLUSH W/WTR FOR SKIN/EYE CONTACT.

=====
Fire Fighting Measures
=====

Fire Fighting Procedures:SCBA TO PROTECT AGAINST
TOX.VAP.(BR,F,HALOG.AC.,CARBONYL HAL

=====
Accidental Release Measures
=====

Spill Release Procedures:VENTILATE AREA,ESPECIALLY LOW PLACES WHERE
HEAVY VAP. MAY COLLECT. REMOVE OPEN FLAMES.

=====
Handling and Storage
=====

Handling and Storage Precautio
ns:STORE IN COOL,DRY WELL VENTED LOW FIRE
RISK AREA. PROTECT FROM HEAT,SHOCK,FRICION. KEEP CONTAINERS
CLOSED.

Other Precautions:DO NOT HEAT ABOVE 125F.AVOID CONT.DAMAGE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE FULL FACE PIECE SUPPL.AIR RESP.OR SCBA IF
TLV EXCEEDED.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN