View NSN Online: https://aerobasegroup.co.il/nsn/6830-01-140-6150

Product ID:HALON 1301, FREON FE 1301 MSDS Date:01/15/1991 FSC:6830 NIIN:01-140-6150 MSDS Number: BGNQW === Responsible Party === Company Name: ANSUL FIRE PROTECTION, WORMALD U.S.INC. Address: ONE STANTON STREET **City:MARINETTE** State:WI ZIP:54143-2542 Country:US Info Phone Num:7 15-735-7411 Emergency Phone Num:715-735-7411/800-424-9300(CHEMTREC) CAGE:03670 === Contractor Identification === **Company Name: ANSUL INC** Address: ONE STANTON STREET Box:City:MARINETTE State:WI ZIP:54143-2542 Country:US Phone:715-735-7411 CAGE:03670 Company Name: DDRV STOCK MAINTENANCE DIV/DDRV-H Address:8000 JEFFERSON-DAVIS HIGHWAY Box:City:RICHMOND State:VA ZIP:23297 Country:US Phone:804-279-3125 CAGE:02LX8 Company Name: FIRE-X CORP Address:3305 CROFT ST Box:City:NORFOLK State:VA ZIP:23513-4903 Cou

ntry:US Phone:775-855-0196 CAGE:6K586 Company Name:FIRE-X OF VA (804-266-8844) Address:6107 STAPLES MILL RD Box:9757 City:RICHMOND State:VA ZIP:23225 Country:US Phone:804-266-8844 CAGE:0FA36

Ingred Name:TRIFLUOROBROMOMETHANE (HALON 1301) (SARA III) CAS:75-63-8 RTECS #:PA5425000 Fraction by Wt: >99% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 Ozone Depleting Chemical:1

============

LD50 LC50 Mixture:LC50=416 GM/CUM (RAT) Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES- THE LIQUID FORM OF THIS MATERIAL CAN PRODUCE CHILLING SENSATIONS AND DISCOMFORT. SKIN- EVAPORATION OF LIQUID FROM THE SKIN CAN PRODUCE CHILLING SENSATIONS. FROSTBITE CAN OCCUR. INHALATION- VAPOR IS HEAVIER THAN AIR AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR BREATHI NG. MAY LEAD TO NARCOSIS, DEATH. Effects of Overexposure: ACUTE: DIZZINESS, IMPAIRED COORDINATION, REDUCED MENTAL ACUITY, AND CARDIAC EFFECTS CAN OCCUR. UNCONSCIOUSNESS OR EVEN DEATH IN HIGH CONCENTRATIONS WITH LONGER EXPOSURES. CHRONIC: NONE KNOWN WHEN OCC UPATIONAL EXPOSURE ARE BELOW THE TLV. Medical Cond Aggravated by Exposure: CARDIAC PROBLEMS. ALSO, PRODUCT IS AN ASPHYXIANT & CAN INDUCE CARDIAC MUSCLE SENSITIZATION TO

CIRCULATING EPINEPHRINE-LIKE COMPOUNDS.

======

First Aid:EYE:FLUSH WITH PLENTY OF WATER FOR 15MIN WHILE HOLDING LIDS OPEN; SKIN:WASH WITH COPIOUS AMOUNTS OF SOAP & WATER FOR AT LEAST 15MIN,IF REDNESS,ITCHING OCCURS,GET MEDICAL ATTN,TREAT FROSTBITE IF NECESS ARY; INH:REMOVE TO FRESH AIR,IF COUGH OROTHER RESPIRATORY SYMPTOMS OCCUR,CONSULT MEDICAL PERSONNEL; ING:NOT LIKELY TO OCCUR.

Flash Point:NO NFLAMMABLE Extinguishing Media:THIS IS A FIRE EXTINGUISHING AGENT. Fire Fighting Procedures:USE WATER TO COOL FIRE-EXPOSED CYLINDERS OR OTHER CONTAINERS. SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:CONTAINERS ARE EQUIPPED WITH PRESSURE AND TEMPERATURE RELIEF DEVICES, BUT RUPTURE MAY OCCUR UNDER FIRE CONDITIONS AND TOXIC DECOMPOSITION BY-PRODUCTS CAN FORM.

Spill Release Procedures: EVACUATE AREA, VENTILATE TO OUTSIDE ATMOSPHERE.COOL OR REMOVE HOT, METAL SURFACES OR SOURCE OF NON-EXTINGUISHED FLAMES.

 Handling and Storage Precautions:STORE AS A LIQUEFIED COMPRESSED GAS IN DOT APPROVED PRESSURE VESSELS AWAY FROM HIGH TEMPERATURE.
Other Precautions:IF CYLINDER IS NOT CONNECTED TO A SYSTEM,IT MUST BE SAFETY CAPPED TO PROTECT AGAINST ACTUATION OF VALVE & RELEASE OF

AGENT.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:NOT NORMALLY NECESSARY IF CONTROLS ARE ADEQUATE.FOR HIGH CONCENTRATIONS EXCEEDING 10%,OR IF EXPOSURE IS PROLONGED,USE POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR. Ventilation:MECHANICAL & LOCAL EXHAUST. Protective Gloves:PLASTIC Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:SAFETY SHOWER & EYE BATH Supplemental Safety and Health

======= Physical/Chemical

Properties =============

HCC:G3

Boiling Pt:B.P. Text:-72F,-58C Melt/Freeze Pt:M.P/F.P Text:-270F,-168C Vapor Pres:199 PSI Vapor Density:5.2 Spec Gravity:1.57 Solubility in Water:NEGLIGIBLE Appearance and Odor:SWEET ODOR, COLORLESS GAS. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES ACTIVE METALS, FIRES OF METAL HYDRIDES, STRONG OXIDIZING AGENTS. Stability Condition to Avoid:EXTREMELY HIGH TEM PERATURES Hazardous Decomposition Products:CO, CO*2,OXIDES OF BROMIDE & FLORIDE,HYDROGEN BROMIDE.

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defe

nse. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.