

XEROX CORPORATION -- 6R301;DRY INK/TONER -- 6850-01-165-5409

===== Product Identification =====

Product ID:6R301;DRY INK/TONER

MSDS Date:04/10/1990

FSC:6850

NIIN:01-165-5409

MSDS Number: BGPND

=== Responsible Party ===

Company Name:XEROX CORPORATION

Address:100 CLINTON AVE SOUTH

Box:1540

City:ROCHESTER

State:NY

ZIP:14644-1877

Country:US

Info Phone Num:800-828-6571

Emergency Phone Num:716-422-21

77

Preparer's Name:MSDS# A-0023

CAGE:26921

=== Contractor Identification ===

Company Name:XEROX CORPORATION

Address:100 CLINTON AVE SOUTH

Box:City:ROCHESTER

State:NY

ZIP:14644-1877

Country:US

Phone:800-828-6571/716-422-2177

CAGE:26921

===== Composition/Information on Ingredients =====

Ingred Name:STYRENE ACRYLATE COPOLYMER

CAS:25213-39-2

Fraction by Wt: >90%

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 5-10%

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3;

Ingred Name:QUATERNARY AMMONIUM SALT (TRADE SECRET)
Fraction by Wt: 10G/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS PRACTICALLY
NON-TOXIC,NON-SENSITIZING,MINIMALLY IRRITATING,NON-MUTAGENIC.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:MINIMAL RESPIRATORY TRACT IRRITATION
MAY OCCUR
AS WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING
RESPIRATORY AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER; SKIN:WASH WITH SOAP & WATER;
INHALATION:REMOVE FROM EXPOSURE; INGESTION:DRINK SEVERAL GLASSES OF
WATER.

===== Fire Fighting Measures =====

Flash Point:NO
NE
Extinguishing Media:WATER,FOAM,DRY CHEMICAL,CARBON DIOXIDE.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.AVOID INHALATION OF SMOKE.
Unusual Fire/Explosion Hazard:THIS POWDER CAN FORM EXPLOSIVE MIXTURES
WITH AIR.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR SWEEP UP SPILLED TONER AND TRANSFER
TO A SEALABLE CONTAINER FOR DISPOSAL.SWEEP SLOWLY TO AVOID
DUSTING,OR USE A V
ACUUM WITH A MOTOR RATED FOR DUST.THE HOSE ON THE
VACUUM SHOULD BE BONDED TO AVOID STATIC.WASH AREA W/SOAP AND
WATER.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID INHALING DUST.
Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.
Ventilation:NORMAL ROOM VENTILATION. (LOCAL EXHAUST IF HANDLING PRODUCT
IN

BULK.)
Protective Gloves:NONE NORMALLY REQUIRED.
Eye Protection:NOT NEEDED IN NORMAL SERVICE.
Other Protective Equipment:GOGGLES & RESPIRATORS MAY BE REQD IN BULK
PROCESS FACILITIES
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.USE REASONABLE
CARE.
Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity: 1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK POWDER,FAINT ODOR

===== Stabilit
y and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:DUST+SOURCES OF IGNITION.
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION MAY BE TOXIC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL REGULATIONS.INCINERATE ONLY IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This infor
mation is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.