

EASTMAN KODAK COMPANY -- 153 2753 FLEXICOLOR DEVELOPER REPLENISHER, PART C --
6750-01-178-4421

===== Product Identification =====

Product ID:153 2753 FLEXICOLOR DEVELOPER REPLENISHER, PART C

MSDS Date:06/22/1994

FSC:6750

NIIN:01-178-4421

MSDS Number: BGPVL

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phon

e Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Inform

ation on Ingredients =====

Ingred Name:4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE
SULFATE

CAS:25646-77-9

RTECS #:KJ6477000

Fraction by Wt: 40-45%

Ingred Name:SODIUM METABISULFITE

CAS:7681-57-4

RTECS #:UX8225000

Fraction by Wt: 1-5%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 50-55%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:PRODUCT CAUSES IRRITATION AND MAY
CAUSE KIDNEY DAMAGE IF INGESTED OR ABSORBED THROUGH SKIN. PRODUCT
(ESPECIALLY AS THE CONCENTRATE) RELEASES SULFUR DIOXIDE,A
RESPIRATORY IRRITANT WITH A TLV OF 2 PPM.

Effects of Overexposure:EYE:IRRITATION. SKIN:IRRITATION AND/OR POSSIBLE
ALLERGIC REACTION. INHALED:IRRITATION. INGESTED:G/I
DISTRESS/IRRITATION.

Medical Cond Aggravated by Exposure:NONE LISTED BY MFR.

===== First Aid Measures

=====

First Aid:EYE:FLUSH WITH WATER,GET MEDICAL ATTENTION. SKIN:FLUSH WITH
WATER.GET MEDICAL ATTENTION IF IRRITATION PERSISTS OR ALLERGY
APPEARS. INHALED:REMOVE TO FRESH AIR.GET MEDICAL ATTENTION IF
SYMPTOMS PERSIST S. INGESTED:RINSE MOUTH,GIVE 2 GLASSES OF
WATER,INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. NOTHING BY
MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:NONE

Upper

Limits:NONE

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE,
"ALCOHOL" FOAM

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO DRAIN WITH LARGE AMOUNT OF WATER.
Neutralizing Agent:NONE LISTED BY MFR.

=====

== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED

Other Precautions:AVOID CONTACT WITH MINERAL ACIDS & ALKALI. KEEP FROM
CONTACT WITH OXIDIZING MATL. AVOID BREATHING VAPORS. USE W/ADEQUATE
VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A
NIOSH APPROVED ACID GAS RESP SHOULD BE WORN IF
NEEDED

Ventilation:GOOD GENERAL VENTILATION OR LOCAL EXHAUST TO CONTROL TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.

Supplemental Safety and Health
KEY1: C1. THIS IS A THREE PART KIT.

===== Physical/Chemical Properties =====

HCC:C2

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vap

or Pres:18

Vapor Density:0.6

Spec Gravity:1.18

pH:2.12

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:REDDISH-BROWN SOLUTION, SULFUR DIOXIDE ODOR

Percent Volatiles by Volume:55 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZERS, STRONG BASES

Stability Condition to Avoid:MOISTURE

Hazardous Decomposition Products:COMBUSTION MAY PRODUCE OXIDES OF
CARBON,SULFUR,& NI

TROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.