View NSN Online: https://aerobasegroup.com/nsn/9160-01-244-6808

MONSANTO CO -- COOLANOL 25R DIELECTRIC HEAT TRANSFER FLUID -- 9160-01-244-6808

========= Product Identification ==============

Product ID:COOLANOL 25R DIELECTRIC HEAT TRANSFER FLUID

MSDS Date:05/01/1986

FSC:9160

NIIN:01-244-6808

MSDS Number: BGRGJ
=== Responsible Party ===

Company Name: MONSANTO CO Address: 800 N. LINDBERGH BLVD

City:ST. LOUIS

State:MO ZIP:63167

Info Phone Num:314-694-1000

Emergency Phone Num:3

14-694-1000

CAGE:76541

=== Contractor Identification ===

Company Name: MONSANTO COMPANY

Address:800 N LINDBERGH BLVD

Box:City:SAINT LOUIS

State:MO ZIP:63167 Country:US

Phone:314-694-6661 OR 800-332-3111

CAGE:76541

======= Composition/Information on Ingredients ========

Ingred Name: ORGANO-SILICATE ESTER

Ingred Name: ANTIOXIDANT ADDITIVE (PROPRIETARY)

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL

CAS:128-37-0

RTECS #:GO7875000 OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3; 9192

Ingred Name:BERYLLI

RTECS #: VV8925000 Other REC Limits: OSHA CEILING 0.005 OSHA PEL:0.002 MG/M3; C,0.005 ACGIH TLV:0.002 MG/M3; A2;8990 Ingred Name: HYDROGEN CHLORIDE (HYDROCHLORIC ACID) (SARA III) CAS:7647-01-0 RTECS #:MW4025000 Fraction by Wt: TRACE **OSHA PEL:C 5 PPM** ACGIH TLV:C 5 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qtv:5000 LBS ============ Hazards Identification ========================= LD50 LC50 Mixture:ORAL RAT LD50 > 15800 MG/KG Routes of Entry: Inhalati on:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic: COOLANOL 25R IS NOT EXPECTED TO PRODUCE ADVERSE HUMAN HEALTH EFFECTS WHEN RECOMMENDED SAFETY PRECAUTIONS. PRODUCT IS A MILD IRRITANT. Explanation of Carcinogenicity: HMTC LETTER OF 5DEC84 LISTED INGRED. 04 AS "ORTHO SILICATE". CAS NO. IS FOR BERYLLIUM SILICATE, A LISTED CARCINOGEN. Effects of Overexposure: EYE/SKIN: MILD IRRITATION. INHALED: RESPIRATORY **IRRITAT** ION. Medical Cond Aggravated by Exposure: NONE REPORTED. First Aid:EYE:FLUSH WITH WATER. SKIN:REMOVE CONTAMINATED CLOTHING, WASH WITH SOAP & WATER. INHALED: REMOVE TO FRESH AIR. INGESTED: GIVE LARGE AMOUNT OF MILK OR WATER. GET MEDICAL ATTENTION. ============= Fire Fighting Measures ======================== Flash Point Method:COC Flash Point:325F/163C Autoignition Temp: Autoignition Temp Text: 480F Extinguishing Me

UM SILICATE (AS BERYLLIUM)

CAS:15191-85-2

dia:WATER SPRAY,FOAM,DRY CHEMICAL,CARBON DIOXIDE OR OTHER AGENT FOR CLASS B FIRE.
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND SELF CONTAINED BREATHING APPARATUS. DECONTAMINATE EQUIPMENT AFTER USE. Unusual Fire/Explosion Hazard:SEE HAZARDOUS DECOMPOSITION PRODUCTS.
========= Accidental Release Measures ==========
Spill Release Procedures:ABSORB ON INERT MATERIAL. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A COOL DRY AREA.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY NEEDED. USE NIOSH ORGANIC VAPOR RESPIRATOR OR SUPPLIED AIR RESPIRATOR IF PRODUCT IS USED AT ELEVATED TEMPERATURES OR IS MISTED.
Ventilation:GENERAL VENTILATION NORMALLY SUFFICIENT. USE LOCAL EXHAUST FOR HIGH EXPOSURE OPERATIONS. Protective Gloves:WEAR PROTECTIVE (RUBBER) GLOVES. Eye Protection:MFR:N
ONE HMIS:SAFETY GLASSES.
Work Hygienic Practices:USE NORMAL, GOOD INDUSTRIAL HYGIENE PRACTICE, AVOIDING UNNECESSARY CONTACT AND REMOVING MTL FROM SKIN, EYES, CLOTHING.
Supplemental Safety and Health INGREDIENTS FROM LETTER TO HMTC 05DEC84.MFR DOES NOT CONFIRM OR DENY USE OF BERYLLIUM SILICATE(1988). SEE DGSC-SLM CASE HISTORY 85089H FOR DETAILS.
======== Physical/Chemical Properties =========
HCC:N1 Vapor Pres: