

LOCTITE CORP AUTOMOTIVE & CONS -- DURO 80249 WHITE PLASTIC RUBB; WPR-1 DURO WHI

=====
MSDS Safety Information
=====

FSC: 8030

NIIN: 00-004-4333

MSDS Date: 03/08/1994

MSDS Num: BGSNY

Product ID: DURO 80249 WHITE PLASTIC RUBB; WPR-1 DURO WHITE PLASTIC RUB.

MFN: 01

Responsible Party

Cage: 08028

Name: LOCTITE CORP AUTOMOTIVE & CONSU

MER GROUP (DURO)

Address: 4450 CRANWOOD PARKWAY

City: CLEVELAND OH 44128-4004

Info Phone Number: 216-663-3011

Emergency Phone Number: 216-663-3011

Preparer's Name: PAULA KINNEY

Review Ind: Y

Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 08028

Name: LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP

Address: 4450 CRANWOOD COURT

City: CLEVELAND OH 44128-4004

=====
Contractor Summary
=====

Cage: 08028

Name: LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP

Address: 4450 CRANWOOD COURT

City: CLEVELAND OH 44128-4004

Phone: 216-663-3011

Cage: 05972

Name: LOCTITE CORPORATION

Address: 1001 TROUT BROOK CROSSING

City: ROCKY HILL CT 06067-3910

Phone: 860-571-5100

=====
Item Description Information
=====

=====
Item Name: SEALING COMPOUND
Specification Number: UNKNOWN
Type/Grade/Class: NONE
Type of Container: TUBE
=====

Ingredients
=====

Cas: 78-93-3
RTECS #: EL6475000
Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
% Wt: 25-30
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM/300STEL;9394
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 64742-89-8
Name: LACOLENE ALIPHATIC SOLVENT (PROPRIETARY)
% Wt: 30-35
Other REC Limits: NONE RECOMMENDED
OSHA PEL:: 400 PPM

Cas: 110-82-7
RTECS #: GU6300000
Name: CYCLOHEXANE (SARA III)
% Wt: <5
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM, 9394
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Name: SYNTHETIC RUBBER (PROPRIETARY)
% Wt: 40-50
Other REC Limits: NONE RECOMMENDED
OSHA PEL: N
OT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Name: PIGMENT (PROPRIETARY)
% Wt: TRACE
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED
=====

Health Hazards Data
=====

LD50 LC50 Mixture: UNKNOWN
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EYE IRR

ITANT. TOXIC BY INGEST/INHAL. CAN IRRITATE NOSE,
THROAT, SKIN & EYES.

Explanation Of Carcinogenicity: PER MSDS:CARCINOGEN:NTP/IARC/
OSHA:NO.

Signs And Symptions Of Overexposure: EXCESSIVE INHALATION CAUSES
HEADACHE,DIZZINESS,NAUSEA,LEADING TO ANESTHESIS IN VERY HIGH CONCENTRATIONS.

Medical Cond Aggravated By Exposure: NONE KNOWN. TARGET ORGANS:LIVER/NERVOUS
SYTEM/RESPIRATORY SYSTEM/GASTROINTESTINAL TRACT.

First Aid: INGEST:DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMED. INHAL:REMOVE TO

FRESH AIR. CALL PHYSICIAN. SKIN:WASH W/LARGE AMTS OF WATER. EYE:FLUSH W/WATER
FOR @LEAST 15MINS. SEEK MED HELP.

=====
Handling and Disposal

=====
Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPARKS. USE ADEQUATE
VENTILATION. AVOID BREATHING VAPORS. CLEAN UP WITH NON-SPARKING TOOLS.

Waste Disposal Methods: LANDFILL OR INCINERATE FOLLOWING EPA & LOCAL
REGULATIONS.

Handling And St

orage Precautions: DO NOT SMOKE. TURN OFF ALL SOURCES OF
IGNITION. VAPORS MAY FLASH & EXPLODE. AVOID PROLONG BREATHING OF VAPORS
& CONTACT WITH SKIN. KEEP AWAY FROM EYES

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====
Fire and Explosion Hazard Information

=====
Flash Point Method: TCC

Flash Point Text: 0F/-18C

Extinguishing Media: DRY POWDER, FOAM, CO2.

Fire Fighting Procedur

es: NONE SPECIFIED BY MANUFACTURER. HOWEVER USE
APPROPRIATE PROT CLOTHING/EQPMT AS CONDITIONS WARRANT.

Unusual Fire/Explosion Hazard: VAPORS MAY CAUSE FLASH FIRE. VAPORS MAY IGNITE
EXPLOSIVELY.

=====
Control Measures

=====
Respiratory Protection: NONE SPECIFIED BY MANUFACTURER.

Ventilation: SUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW TLV.

Protective Gloves: RUBBER OR PLASTIC GLOVES

Eye P

rotection: SAFETY GLASSES OF GOGGLES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH HANDS AFTER HANDLING. USE GOOD CHEMICAL HYGIENE PRACTICE.

Physical/Chemical Properties

HCC: F2

B.P. Text: 150F,66C

Vapor Pres: 50 MM

Vapor Density: >1

Spec Gravity: 1.0

Solubility in Water: NEGLIGIBLE

Appearance and Odor: WHITE LIQUID,KETONE ODOR

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER. HOWEVER AVOID ALL SOURCES OF IGNITION.

Materials To Avoid: STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: NON-THERMAL:NONE KNOWN. FIRE/THERMAL:OXIDES OF CARBON.

Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 08028

Trans ID NO: 43318

Product ID: DURO 80249 WHITE PLASTIC RUBB; WPR-1 DURO WHITE PLASTIC RUB.

MSDS Prepared Date: 03/08/1994

Review Date: 03/01/1995

MFN: 1

Net Unit Weight: 4 OZ

Multiple KIT Number: 0

Review IND: Y

Type Of Co

Container: TUBE

Additional Data: PER MSDS:DOT PROPER SHIPPING NAME:FLAMM LIQUIDS, CLASS 3,
IATA:FLAMM LIQ, CLASS 3, UN1133.

=====
Detail DOT Information
=====

DOT PSN Code: AFR
DOT Proper Shipping Name: ADHESIVES,
DOT PSN Modifier: CONTAINING A FLAMMABLE LIQUID
Hazard Class: 3
UN ID Num: UN1133
DOT Packaging Group: II
Label: FLAMMABLE LIQUID
Special Provision: B52,T,T30
Packaging Exception: 150
N
on Bulk Pack: 173
Bulk Pack: 242
Max Qty Pass: 5 L
Max Qty Cargo: 60 L
Vessel Stow Req: B

=====
Detail IMO Information
=====

IMO PSN Code: AIH
IMO Proper Shipping Name: ADHESIVES,
IMO PSN Modifier: CONTAINING A FLAMMABLE LIQUID o
IMDG Page Number: 3174
UN Number: 1133
UN Hazard Class: 3.2
IMO Packaging Group: I/II*
Subsidiary Risk Label: -
EMS Number: 3-05
MED First Aid Guide NUM: 330

=====
Detail IATA Information
=====

IATA PSN Code: AKY
IATA UN ID Num: 1133
IATA Proper Shipping Name: ADHESIVES
IATA PSN Modifier: ,CONTAINING FLAMMABLE LIQUID
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: II
Packing Note Passenger: 305
Max Quant Pass: 5L
Max Quant Cargo: 60L
Packaging Note Cargo: 307
Exceptions: A7

=====
Detail AFI Inform

ation

=====
AFI PSN Code: AKY
AFI Proper Shipping Name: ADHESIVES
AFI PSN Modifier: ,CONTAINING FLAMMABLE LIQUID
AFI Hazard Class: 3
AFI UN ID NUM: UN1133
AFI Packing Group: II
Special Provisions: P5
Back Pack Reference: A7.3
=====

HAZCOM Label

=====
Product ID: DURO 80249 WHITE PLASTIC RUBB; WPR-1 DURO WHITE PLASTIC RUB.
Cage: 08028
Company Name
: LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP
Street: 4450 CRANWOOD COURT
City: CLEVELAND OH
Zipcode: 44128-4004
Health Emergency Phone: 216-663-3011
Label Required IND: Y
Date Of Label Review: 03/01/1995
Status Code: C
Label Date: 03/01/1995
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Health Hazard: Moderate
Contact Hazard: Moderate
Fire Hazard: Severe
Reactivity Hazard: None
Hazard And Precautions: EYE IRRITANT. TOXIC BY INGEST/INHAL. CAN IRRITATE NO
SE,
THROAT, SKIN & EYES. DO NOT SMOKE. TURN OFF ALL SOURCES OF IGNITION.
VAPORS MAY FLASH & EXPLODE. AVOID PROLONG BREATHING OF VAPORS &
CONTACT WIT H SKIN. KEEP AWAY FROM EYES. TARGET ORGANS:GASTROINTESTINAL
TRACT/LIVER/RESPIRATORY SYS/NERVOUS SYSTEM. FIRST AID: INGEST:DO NOT INDUCE
VOMITING. CALL PHYSICIAN IMMED. INHAL:REMOVE TO FRESH AIR. CALL PHYSICIAN.
SKIN:WASH W/LARGE AMTS OF WATER. EYE:FLUSH W/WATER FOR @LEAST 15MINS. SEEK
MED HELP.
=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States

of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.