

Product ID:FE-7004-B RESIWELD MSDS Date:02/14/1989 FSC:8040 NIIN:00-062-4173 Kit Part:Y MSDS Number: BGTJP === Responsible Party === Company Name: H.B.FULLER COMPANY Address:1200 WOLTERS BLVD **City:VADNAIS HEIGHTS** State:MN ZIP:55110 Info Phone Num:612-481-3000 Emergency Phone Num:612-481-3000 OR 612-481-1588 Preparer's Name: JOHN DOLMAR, CIH CAGE: JO875 === Contractor Identification === Company Name: H.B. FULLER COMPANY Address:3500 LEXINGTON AVENUE N. Box:City:ST. PAUL State:MN ZIP:55126-8076 Country:US Phone:612-236-5300/ -5309 FAX CAGE:0DH19 Company Name: H.B.FULLER COMPANY CAGE: JO875

Ingred Name:POLYAMIDE RESIN Fraction by Wt: >10%

Ingred Name:TRIETHYLENE TETRAAMINE CAS:112-24-3 RTECS #:YE6650000 Fraction by Wt: >10%

=====

LD50 LC50 Mixture:NO INFORMATION PROVIDED. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: RESPIRATORY IRRITANT; SEVERE SKIN & STRONG EYE IRRITANT; DERMAL SENSITIZER; CHRONIC:NONE ANTICIPATED. Effects of Overexposure: EYES: STRONG IRRITANT; SKIN: CONTACT WILL CAUSE SEVERE IRRITATION. STRONG DERMAL SENSITIZER; INHAL:MAY CAUSE **RESPIRATORY IRRITATION.** Medical Cond Aggravated by Exposure: DERMATITIS DUE TO SENSITIZATION. First Aid:EYES:FLUSH IMMEDIATELY W/ WATER FOR 15 MINS-GET MED ATTN. IF IRRITATION PERSISTS; SKIN:WASH AFFECTED AREA W/ SOAP & WATER. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE; INHAL:REMOVE FROM EXPOSURE. RESTO RE BREATHING IF NECESSARY. KEEP WARM & QUIET. GET MED ATTN. ================== Fire Fighting Measur Flash Point Method:TCC Flash Point:>200F/>93.3C Extinguishing Media: USE WATER SPRAY, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. Fire Fighting Procedures: PERSONS EXPOSED TO PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING APPARATUS & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:NONE KNOWN. Spill Release Procedures: WEAR RUBBER GLOVES & WIPE UP W/INERT ABSORBENT MATERIAL. RESIDUE MAY BE REMOVED W/ CHLORINATED SOLVENT. Handling and Storage Precautions: STORE IN A COOL, DRY LOCATION. AVOID SKIN CONTACT W/PRODUCT AT ALL TIMES. Other Precautions: USE MATERIAL IN MANNER PROVIDED BY INSTRUCTIONS. Respiratory Protection: IF ENGINEERING CONTROL DO NOT MAINTAIN INHALATION EXPOSURES BELOW PEL/TLV, USE NIOSH/MSHA APPROVED RESPI

RATOR AS PER CURRENT 29CFR1910.134, INSTRUCTIONS/WARNINGS & NIOSH-RESPIRATOR DECISION LOGIC PUB #87-108. Ventilation: PROVIDE SUFFICIENT GENERAL/LOCAL EXHAUST VENTILATION IN PATTERN/VOLUME TO CONTROL INHALATION EXPOSURE BELOW PEL/TLV. Protective Gloves: IMPERVIOUS TYPE FOR TASK AT HAND. Eye Protection:SAFETY GLASSES. Other Protective Equipment: AS REQUIRED FOR TASKS AT HAND TO MINIMIZE EXPOSURE & ENHANCE WORKER PROTECTION (EG. EYE-WASH STATION, ETC). Work Hygienic Practices: USE IN MANN ER SET FORTH BY MFR'S DIRECTIONS AS WELL AS PROCEDURES SET FORTH BY SAFETY & HEALTH OFFICE. Supplemental Safety and Health WARNING STATEMENTS: VAPORS HARMFUL-STRONG SENSITIZER. SEVERE EYE & SKIN IRRITANT. KEY1:J6. Spec Gravity:0.96 Viscosity:5500 CPS Appearance and Odor:LIQUID Stability Indicator/Materials to Avoid:YES NONE ESTABLISHED. Stability Co ndition to Avoid:MFR CITES NONE Hazardous Decomposition Products: IN COMPLETE COMBUSTION CAN YIELD LOW MOLECULAR WEIGHT HYDROCARBONS, CARBON MONOXIDE, & NITROGEN COMPOUNDS.

Waste Disposal Methods:PRODUCT IS A DOT CORROSIVE. IT DOES NOT,HOWEVER,MEET THE RCRA' DEFINITION OF CORROSIVE WASTE. CONSULT H.B. FULLER ENVIRONMENTAL SERVICES 612-481-1588 FOR CURRENT DISPOSAL RECOMMENDATIONS.

Disclaimer (provided wit

h this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.