

MET-L-CHEK COMPANY -- E-57 EMULSIFIER -- 6850-01-268-8788

===== Product Identification =====

Product ID:E-57 EMULSIFIER

MSDS Date:01/01/1997

FSC:6850

NIIN:01-268-8788

Kit Part:Y

MSDS Number: BGTLJ

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Info Phone Num:310-450-1111

Emergency Phone Num:310-450-1111/800-42

4-9300(CHEMTREC)

CAGE:98733

=== Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON/MINERAL OIL, PETROLEUM DISTILLATE,
SOLVENT REFINED (SEVERE), HEAVY NAPHTHENIC

CAS:64741-96-4

RTECS #:PY8040001

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL M

IST
ACGIH TLV:5 MG/M3 AS OIL MIST

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: EYE, SKIN, RESPIRATORY
& GI TRACTS. ACUTE- EYE CONTACT IS NON-IRRITATING. MAY CAUSE SLIGHT
SKIN IRRITATION. VAPORS OR OIL MISTS MAY CAUSE RESPIRATORY TRACT
IRRITATION. INGESTION
MAY RESULT IN VOMITING. ASPIRATION HAZARD.
CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NAUSEA, VOMITING
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGAVATED BY EXPOSURE TO THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: MOVE TO FRESH
AIR. PROVIDE OXYGEN IF NEEDED. EYES: FLUSH WITH WATER FOR 15
MINUTES, HOLDING EYELIDS OPEN. SKIN: FLUSH WITH WATER & WASH SKIN
WITH SOAP & WATER. ORAL: DO NOT INDUCE VOMITING. SEEK MEDICAL
ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT
ASPIRATION.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:>200F,>93C
Extinguishing Media:WATER FOG, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE
DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED.
Fire Fighting Procedures:IN CONFINED AREA, DO NOT ENTER WITHOUT A FULL
BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-
CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA.
STOP LEAK IF POSSIBLE. USE PUMP TO TRANSFER LARGE SPILLS TO
CONTAINER. REMAINING LIQUID/SMALL SPILLS CAN BE TAKEN UP ON SAND,
CLAY, EARTH & SHOVELD INTO CONTAINERS. PREVENT

RUN-OFF TO ENTER
WATERWAYS, SEWERS
Neutralizing Agent:NOT RELEVANT

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, IGNITION SOURCES.
STORE IN COOL & VENTILATED LOCATION. DO NOT STORE NEAR OXIDIZING
MATERIAL. AVOID PHYSICAL DAMAGE.
Other Precautions:AVOID BREATHING MISTS. DO NOT GET IN EYES, ON SKIN OR
ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR
DRINKING. REMOVE CONTAMINATED CLOTH
ING PROMPTLY. LAUNDRER BEFORE
REUSE. KEEP OUT O F REACH OF CHILDREN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFINED
AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES
EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED
ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)
Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV
REQUIREMENTS

Protective Gloves:NITRILE RECOMMENDED
Eye Protection:GOGGLES RECOMMENDED
Other Protective Equipment:EYE WASH FOUNTAINS, SAFETY SHOWER AND
CLOTHING TO MINIMIZE SKIN CONTACT
Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.
Supplemental Safety and Health
KEY1:V6. THIS PRODUCT IS A KIT CONSISTING OF PENETRANT AND EMULSIFIER.
FOR PENETRANT, SEE PNI A, SAME NSN.

=====
Physical/Chemical Properties
=====

HCC:V6
NRC/
State Lic Num:NOT RELEVANT
Boiling Pt:B.P. Text:400F,204C
Spec Gravity:ABOUT 0.92
Solubility in Water:EMULSIFY
Appearance and Odor:PINK OILY LIQUID - SLIGHT HYDROCARBON ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL
Stability Condition to Avoid:HEAT, IGNITION SOURCES.
Hazardous Decomposition Products:CARBON MONOXIDE AND OTHER UNIDENTIFIED
ORGANIC COMPOUNDS.

=====
Disposal Considerations

=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATION RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document s

ould seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.