

CHEMRAY COATING CORP -- ENAMEL ALKYD GLOSS(FOR EXT&INT)GREEN 14062 --
8010-00-298-2296

=====
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS(FOR EXT&INT)GREEN 14062

MSDS Date:10/28/1988

FSC:8010

NIIN:00-298-2296

MSDS Number: BHDKX

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:20

1-245-1111

Emergency Phone Num:201-245-1111

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

Fraction by Wt: 48%

ACGIH TLV:200 PPM

Ingred Name:LEAD AS (PB), LEAD PRIMER

Fraction by Wt: .2%

ACGIH TLV:.05 MG/M3

Ingred Name:CHROME YELLOW AS (PB CR04)

Fraction by Wt

: 9.8%
ACGIH TLV:.05 MG/M3

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:HIGH VAPOR CONCENTRATIONS (OVER 1000 PPM) ARE IRRITATING TO THE EYE & RESPIRATORY TRACT.MAY CAUSE HEADACHES & DIZZINESS-PROLONG SKIN CONTACT IRRITATES.
Explanation of Carcinogenicity:NA
Effects of Overexposure:NA
Medical Cond Aggravated by Exposure:NA

=====
First Aid Measures
=====

First Aid:EYE CONTACT FLUSH W/WTR FOR 15 MINS OR UNTIL IRRITATION SUBSIDES.IF IRRITATION PERSISTS CALL A PHYSICIAN.SKIN CONTACT REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY W/SOAP & WTR.INHALATION IF OVERCOM E BY VAPORS,REMOVE TO FRESH AIR,CALLPHYSICIAN.INGESTION DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:103F 39.44C
Lower Limits:.9
Upper Limits:7
Extinguish
ing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIP FOR ENCLOSED CONTAINERS W/WTR SPRAY, AVOID BREATHING OR FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED,USE WTR SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.KEEP FROM HEAT,SPARKS & OPEN FLAME.ASS ABSORBENT (SAND,EARTH,SAWDUCT)TO SPIL.VENTILATE AREA.IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIKING.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

=====
Handling and Storage
=====

Handling and Storage Precautions:PROPER SHIPPING NAME PAINT
HAZARDOUS CLASSIFICATION COMBUSTIBLE LIQUID ID NO UN1263
Other Precautions:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATION OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMA

GE.INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING &
INHALAING THE CONTENTS M AY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATORY IN CONFINED AREA.

Ventilation:LOCAL EXHAUST EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEM-RESISTANT GLOVES

Eye Protection:SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:USE CHEM RESISTANT APRON OR OTHER CLOTHING
TO AVOI

D REPEATED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER-USE & KEEP
CONTAINER CLOSED WHENNOT IN USE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308F

Melt/Freeze Pt:M.P/F.P Text: