

EVERSEAL MANUFACTURING CO., INC. -- RED GLOSS ALKYD ENAMEL 11105-1 -- 8010-00-616-7486

===== Product Identification =====

Product ID:RED GLOSS ALKYD ENAMEL 11105-1

MSDS Date:04/29/1987

FSC:8010

NIIN:00-616-7486

MSDS Number: BHDRD

=== Responsible Party ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

Address:475 BROAD AVENUE

City:RIDGFIELD

State:NJ

ZIP:07657

Country:US

Emergency Phone Num:201-94

3-4986

CAGE:EO432

=== Contractor Identification ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

CAGE:EO432

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 38%

Ingred Name:RED PIGMENT

CAS:2425-85-6

Fraction by Wt: 11%

Ingred Name:MINERAL SPIRITS

(VAPOR PRESSURE 5)

CAS:64475-85-0

RTEC

S #:PY8240000
Fraction by Wt: 50%
OSHA PEL:120 PPM
ACGIH TLV:5G/KG (ORAL)

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:INHALATION: DIZZINESS, NAUSEA, POSSIBLLE
UNCONSCIOUSNESS. SKIN/EYES: IRRITATION

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION
IF NECESSARY. SKIN: WASH WITH SOAP
AND WATER
EYES: FLUSH WITH WATER.CONSULT A
PHYSICI AN

=====
Fire Fighting Measures
=====

Flash Point:105F/40.56C
Upper Limits:1
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING
MEDIUM. FIREFIGHTERS SHOULD WEAR S.C.B.A.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE ADEQUATE
VENTILA- TION. ABSORB
SMALL SPILLS ON DRY ABSORPTION
MATERIAL. USE SPARK PROOF SCOOP FOR LARGER SPILLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION
SOURCES.
Other Precautions:NPCA/HMIS RATING 3,2,0,H

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF TLV MAY BE EXCEEDED, USE CARTRIDGE FUME MASK
Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED
Protective Gloves:l

MPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN W/CLOTHING OR BARRIER CREAM

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323-390F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avo

id:NA

Hazardous Decomposition Products:CARBON MONOXIDE AND/OR CARBON DIOXIDE
ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS PER LOCAL AND FEDERAL REGULATIONS
FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, wa
rrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.