

NATINAL AEROSOL PRODUCTS COMPANY -- ENAMEL FLAT BLACK 37038 AEROSOL --
8010-00-067-5437

=====
===== Product Identification =====

Product ID:ENAMEL FLAT BLACK 37038 AEROSOL

MSDS Date:05/26/1988

FSC:8010

NIIN:00-067-5437

MSDS Number: BHFLL

=== Responsible Party ===

Company Name:NATINAL AEROSOL PRODUCTS COMPANY

Address:2103 E. 14TH STREET

City:LOS ANGELES

State:CA

ZIP:90021

Country:US

Emergency Phone Nu

m:(213) 627-2668

CAGE:JO968

=== Contractor Identification ===

Company Name:NATINAL AEROSOL PRODUCTS COMPANY

Address:2103 E. 14TH STREET

City:LOS ANGELES

State:CA

ZIP:90021

Country:US

CAGE:JO968

Company Name:NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

Address:2193 E 14TH STREET

Box:City:LOS ANGELES

State:CA

ZIP:90021-2843

Country:US

CAGE:59986

=====
===== Composition/Information on Ingredients =====

Ingred Name:VM &P NAPHTHA

CAS:8030-30-6

RTECS #:QI9450000

Fraction by Wt: 40%

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 35%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTANE
CAS:75-28-5
Fraction by Wt: 25%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:INHL:HEADACHE, NAUSEA, & DIZZINESS.
SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSEIRRITATION.

=====
= First Aid Measures =====

First Aid:INHL:MOVE TO FRESH AIR. SKIN:FLUSH W/LARG AMOUNTS OF WATER.
REMOVE CONTAMINATED CLOTHING. EYE: FLUSH W/WATER FOR 15 MINS.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:58F/14.44C
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE
WORN BY FIREFIGHTERS
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS
EXPOSED TO FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS, EXTINGUISH IGNITION
SOURCEIN IMMEDIATE AREA. AVOID CONTACT W/LIQUID

=====
===== Handling and Storage =====

Handling and Storage Precautions:DONOT STORE AT ELEVATED TEMPERATURE
Other Precautions:CLOSE CONTAINERS AFTER USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory

Protection:ADEQUATE VENTILATION IS REQUIRED
Ventilation:PROVIDE SUFFICIENT VENTILATION TO KEEP CONCENTRATION
BELOW GIVEN TLV
Protective Gloves:REQUIRED PROLONGED/REPEATED CONTACT
Eye Protection:SOLVENT RESISTANT
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING
Work Hygienic Practices:NONE LISTED
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

HCC:V3
Boiling Pt:B.P. Text:250-310
Vapor Density:>AIR
Spec Gravity:.999
Evaporat
ion Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:BLACK,MOBILE LIQUID CONTAINING VOLATILE SOLVENTS
Percent Volatiles by Volume:76.13

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIALS, RUBBER SOFTENS
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN CLOSED
CONTAINERS AWAY FROM
IGNITIONSOURCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of t

his information to their particular situation.