View NSN Online: https://aerobasegroup.com/nsn/6810-00-687-8429

Product ID:METHYL ETHYL KETONE MSDS Date:09/17/1986 FSC:6810 NIIN:00-687-8429 MSDS Number: BHFRT === Responsible Party === Company Name:CSD INC. Address:5 HACKBERRY LANE Box:687 City:CONROE State:TX ZIP:77305 Country:US Info Phone Num:409-756-1065 Emergency Phone Num:409-756-1065 OR 704-821-9822 CAGE: JO933 === Contractor Identification === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 Company Name:CSD INC. Address:5 HACKBERRY LANE Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE: JO933 Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000

Fraction by Wt: 99.0

% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2737 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CNS EFFECTS LIKE HEADACHE,DIZZINESS,NAUSEA,VOMITING AND POSSIBLE UNCO NSCIOUSNESS;REDNESS OR BURNS OF EYES/SKIN POSSIBLE.CHRONIC:DRYING OF SKIN,D EFATTING OR DERMATITIS. Explanation of Carcinogenicity:DATA PER MSDS Effects of Overexposure:SEE HEALTH HAZARDS DATA. Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALATION:REMOVE TO FRE SH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:20.0F,-6.7C Autoignition Temp:Autoignition Temp Text:960F Lower Limits:10.0 Upper Limits:18.0 Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:CONSIDERED SERIOUS FIRE HAZARDS BECAUSE OF ITS LOW FLASH POINT, HIGH VOLATILITY, AND HEAVY VA POR.

	Accidental	Release	Measures	
--	------------	---------	----------	--

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES ;CONTAIN FREE MATERIAL IF POSSIBLE;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Neutralizing Agent:NOT APPLICABLE.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAIN

ERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT

CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST OR AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED

AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.
Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER
Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK
CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.
Supplemental Safety and Health
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON
SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

HCC:F2
Boiling Pt:=79.4C, 175.F
Vapor Pres:78MM HG
Vapor Density:2.5
Spec Gravity:0.8064
Evaporation Rate & amp; Reference:5.7(N-BUTYL ACETATE = 1)
Solubility in Water:APPRECIABLE
Appearance and Odor:COLORLESS LIQUID, ACETONE LIKE ODOR
Percent Volatiles by Volume:100,0

Stability Indicator/Materials to Avoid

:YES STRONG OXIDIZING AGENTS,CHLORINATED HYDROCARBONS IN PRESENCE OF ALKALIES;ALKANOLAMINE,AMINES,INORGANIC ACIDS,AMMONIA. Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND OTHER UNIDENTIFIED COMPONENTS.

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this inform ation to their particular situation.