NILES CHEMICAL PAINT COMPANY -- N 1207A EARTH YELLOW CAMO TYPE IV -- 8010-01-130-3346

Product ID:N 1207A EARTH YELLOW CAMO TYPE IV MSDS Date:10/11/1989 FSC:8010 NIIN:01-130-3346 Kit Part:Y **MSDS Number: BHNDN** === Responsible Party === Company Name: NILES CHEMICAL PAINT COMPANY Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Info Phone Nu m:616-683-3377 (INFORMATION) Emergency Phone Num:219-236-5856 (24 HOURS) Preparer's Name: MIKE LICHATOWICH CAGE:02388 === Contractor Identification === **Company Name:NILES CHEMICAL PAINT** Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Phone:616-683-3377/219-236-5856 CAGE:02388

======= Composition/Information on Ingredients ==========

Ingred Name:PM ACETATE (VP 3.7 MM HG @ 20C) CAS:108-65-6 RTECS #:AI8925000 Fraction by Wt: 17%

Ingred Name:POL

YESTER RESIN Fraction by Wt: 16%

Ingred Name:N-BUTYL ACETATE (SARA III) CAS:123-86-4 RTECS #:AF7350000 Fraction by Wt: 9% OSHA PEL:150 PPM/200 STEL ACGIH TLV:150 PPM/200STEL;9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 7% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 3% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:CHROMIUM (III) OXIDE CAS:1308-38-9 RTECS #:GB6475000 Fraction by Wt: 1% OSHA PEL:0.5 MG/M3 (CR) ACGIH TLV:0.5 MG/M3 (CR); 8990

Ingred Name:VOC. ORGANIC CMPD 4.33 LB/GAL LESS WATER & NPRS\* (NK) G/L LESS WATER VOC. (NK) LB/GAL SOLIDS (NK) G/L SOLIDS CALCU RTECS #:9999999VO

R

outes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:HISTOLOGIC FIBROSIS OF LUNGS, INCOHERENCE, CORNEAL VACUOLIZATION, ANOREXIA. TAR-GET ORGANS: CNS, LUNGS, EYES, SKIN, RESPIRATORY SYS, GI TRACT, BLOOD, LIVER, **KIDNEYS.ALSO SEE BELOW** Explanation of Carcinogenicity:NOT LISTED Effects of Overexposure: EYE: SEVERE IRRI, LACRIMATION, RED, BLURRED VISION. SKIN: RED & IRRI, DEFATTING OF SKIN, DERMATI TIS. BREATH: NASAL & RESPIRATORY IRRI, CNS DEPRESS (DIZZ, DROWS, WEAK, FATIGUE, CONF) NAUSEA, HEAD, VERTI GO, UNCONSC, ASPHYX. INGES: GASTROINTESIRRI, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA First Aid:INHAL: REMOVE TO FRESH AIR AT ONCE. IF BREATH STOPPED, CPR, GET MED ATTN IMMD. SKIN: IMMED FLUSH W/PLENTY OF WTR. REMOVE CONTAM CLOTHES & FLUSH SKIN W/WTR, GETMED ATTN, LAUNDER CLOTHES & SHOES BEFORE

REUSE. EYE: IMMED FLUSH LG AMTS OF WTR15 MIN, LIFTING LIDS. GET MED ATTN IMMED. CONTACT LENS SHOULD NOT BE WORN. INGESDRINK 1/2 GLASSES WATER. DO NOT INDUCE VOMIT. GET MED ATTN/POISON CC IMMEDIATELY

Flash Point Method:TCC Flash Point:20 F/ -6 C Lower Limits:1.0 Upper Limits:10 Extinguishing Media:DRY CHEMICAL, FOAM, CO2 Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS W/FULL FACEPIECE OPERATED POS ITIVE PRESSURE & FULL PROT CLOTHES. WTR TO COOL CLOSED CONTAIN PREVENT PRESSURE BUILDUP/EXPLOS Unusual Fire/Explosion Hazard:KEEP CONT TIGHTLY CLOSED. VAPORS HEAVIER THAN AIR, MAY TRAVEL ALONG GROUND TO IGNITE SOURCE. ISOLATE FROM HEAT, ETC. OVEREXP TO DECOMP MAY CAUSE HEALTH HAZARDS

Spill Release Procedures: ELIM ALL IGNITION SOURCES. MIN BREATHING OF VAPORSAVOID SKIN CONTACT. ABSORB W/INERT MATERIAL; CLAY, SOI

L, OR

COMMERCIALLY AVAIL ABSORBENT. SHOVEL RECLAIMED LIQ/ABSORBENT INTO RECOVERY OR SALVAGE DRUMS FOR DISPOSAL. LG: DIKE, RECLAIM IN DRUM,TANK,TRUCK

Handling and Storage Precautions: AVOID STORAGE IN HIGH TEMP AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USEAVOID ROUGH HANDLING.

Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME ORCUT

ON EMPTY DRUMS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITOR DEMO VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR USE

Ventilation:SUFFICIENT VENT IN VOL/PATTERN TO KEEP AIR CONCEN BELOW CURRENT APPL OSHA PERMISSIBLE LIMIT. REMOVE DECOMP PRODUCTS Protective Gloves:CHEMICAL RESISTANT GLOV

ES

Eye Protection: CHEM GOGGLES/SAFETY GLASSES/FACE SHIELD

Other Protective Equipment:WEAR CHEMICAL RESISTANT CLOTHING AS NEEDED TO PREVENT SKIN CONTACT. REMOVE CLOTHES THAT BECOME WET (FLAMMABLE HAZARD)

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING RESTROOM. WASH PROMPTLY WHEN SKIN BECOMES CONTAMINATED. Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. DURIN

**G EMERGENCY** 

CONDITIONS, OVEREXP TO DECOMP PRODUCTS MAY CAUSE A HEALTH HAZAR D. SYMPTOMS MAY NOT BE IMMEDIATELY APPA-RENT. OBTAIN MEDICAL ATTENTION.

HCC:F2 Boiling Pt:B.P. Text:175-302 F Decomp Temp:Decomp Text:NE Vapor Density:> AIR Viscosity:70-85 KU Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:SLIGHT Appearance and Odor:LIQUID, ODOR OF SOLVENTS Percent Volatiles by Volume:57.72

=====

Stability Indicator/Materials to Avoid:YES

- STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDES
- Stability Condition to Avoid:UNDER REASONABLE CONDITIONS OF STORAGE AND USE
- Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE
- Conditions to Avoid Polymerization:HIGH TEMPERATURES, SHOCK FROM DROPPING

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsib ility for the suitability of this information to their particular situation.