View NSN Online: https://aerobasegroup.co.il/nsn/3439-01-213-0203

Product ID:FLOWCREAM SOLDER PASTES MSDS Date:06/16/1989 FSC:3439 NIIN:01-213-0203 **MSDS Number: BHPNB** === Responsible Party === Company Name: FEDERATED-FRY METALS INC DIV OF COOKSON AMERICA Address:6TH AVE AND 41ST ST City:ALTOONA State:PA ZIP:16602 Country:US Info Pho ne Num:814-946-1611 Emergency Phone Num:814-946-1611 CAGE:65172 === Contractor Identification === Company Name: FRY TECHNOLOGY DIV OF COOKSON AMERICA INC Address:6TH AVE AND 41ST ST Box:City:ALTOONA State:PA ZIP:16602 Country:US Phone:814-946-1611 CAGE:65172 Ingred Name:TIN CAS:7440-31-5 RTECS #:XP7320000 Fraction by Wt: 0-92% OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192 Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF752500

0 Fraction by Wt: 0-90% OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Fraction by Wt: 0-5% OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:ROSIN ACID CAS:8050-09-7 Fraction by Wt: 4-8%

Ingred Name: OTHER COMPONENTS (TYPE NOT SPECIFIED)

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000 Fraction by Wt: 0-50%

Ingred Name:DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE CAS:124-17-4 RTECS #:KJ9275000 Fraction by Wt: 4-8%

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND RESPIRATORY TRACT;LEAD MAY CAUSE CNS EFFECTS AND KIDNEY DAMAGE,STOMACH PAIN OR CRAMPS AND NAUSEA POSSIBLE. Explanation of Carcinogenicity:DATA PER MSDS Effects of O verexposure:EXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. WATERY EYES, HEADACHE, BREA THING DIFFICULTY, FREQUENT COUGHING AND/OR CHEST PAINS MAY OCCURE FROM ACUTE EXPOSURE. TOXIC GASES CAN BE FATAL.

Medical Cond Aggravated by Exposure:SOME WORKERS MAY BE AFFECTED BY A PRE-EXISTING CONDITION OR OTHER OCCUPATIONAL ILLNESS BECAUSE OF THE WIDE VAR

IATION IN INDIVIDUAL SUSCEPTIBILITIES.

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

Flash Point Method:COC

Flash Point:240F,116C

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE EXPECTED ;FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION

OF HAZARDOUS DECOMPOSITION PRODUCTS.

Spill Release Procedures: CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSU RE.

Handling and Storage Precautions:STORE IN COOL AND DRY AREA.KEEP AWAY FROM H EAT,OPEN FLAMES,SPARKS DIRECT SUNLIGHT. Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR

WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS. Ventilation: USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO

KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE Protective Gloves: PVC OR RUBBER

Eye Protection: GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment: FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTI

NG OR WELDING.

Work Hygienic Practices: WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDER CONTAMINATIED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THEPRESENCE OF CONTAMINENTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.

=====

HCC:N1

Boiling Pt:B.P. Text:>450F,>232C Vapor Pres:0.01 Vapor Density:7 Solubility in Water:SLIGHT Appearance and Odor:GREY PASTES Percent Volatiles by Volume:4-8

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS,REDUCING AGENTS,STRONG ACIDS. Stability Condition to Avoid:HIGH TEMPERATURES Hazardous Decomposition Products:MIXED ORGANICS,LEAD FUMES,ETC.

=

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS OR RETURN TO THE MFG FOR REPROCESSING OF METAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.