

CHEMRAY COATINGS -- PAINT, EXTERIOR, DULL BLACK 51518 -- 8010-00-286-7854
===== Product Identification =====

Product ID:PAINT, EXTERIOR, DULL BLACK 51518
MSDS Date:01/01/1987
FSC:8010
NIIN:00-286-7854
MSDS Number: BHRGP
=== Responsible Party ===
Company Name:CHEMRAY COATINGS
Address:209 N. MICHIGAN AVENUE
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Info Phone Num:201-245-1111/800-924-7854 CHE
MTRAC
Emergency Phone Num:201-245-1111/800-924-7854 CHEMTRAC
Preparer's Name:FRED ARMSTRONG
CAGE:OBRN9
=== Contractor Identification ===
Company Name:CHEMRAY COATING CORP
Address:209 N MICHIGAN AVE
Box:City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:201-245-1111
CAGE:33832
Company Name:CHEMRAY COATINGS CORP.
Address:209 N. MICHIGAN AVE.
Box:NA
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:800-924-9300
CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ing

red Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 40%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:LEAD DRIER
Fraction by Wt: 0.25%
OSHA PEL:.05 MG/M3
ACGIH TLV:.15 MG/M3

Ingred Name:COBALT DRIER
Fraction by Wt: 0.15%
OSHA PEL:.3 MG/M3
ACGIH TLV:.1 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NAUSEA, HEADACHES, DIZZINESS CAUSED BY
OVER INHALATION.
Effects of Overexposure:NAUSEA, HEADACHES, DIZZINESS CAUSED BY OVER
INHALATION.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER.
INHALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR & CALL A
PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:103 F/39 C
Lower Limits:0.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPOR OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER

SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, KEEP FROM HEAT, SPARKS & OPEN FLAMES, ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA (OPEN WINDOWS, DOORS) LARGE SPILL: KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIKING, ADVISE AUTHORITIES.

===== Handling and Storage =====

Handling and Storage

Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY VENTILATED AREA. AVOID DIRECT SUNLIGHT AND EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST FACE VELOCIT Y 60PPM. SPECIAL USE ONLY WITH ADEQUATE VENTILATION. MECHANICAL USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:CHEMICAL SPLASH GOGGLES/FACE SHIELDS.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING, SANDING OR BLASTING DUST.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Te

xt:308 F/153 C

Vapor Pres: