

DEXTER ELECTRONIC MTLs DIV.,THE DEXTER CORP. -- HYSOL PC20M ACRYLIC RESIN --  
5970-00-442-0272

===== Product Identification =====

Product ID:HYSOL PC20M ACRYLIC RESIN

MSDS Date:02/02/1989

FSC:5970

NIIN:00-442-0272

MSDS Number: BHWJC

=== Responsible Party ===

Company Name:DEXTER ELECTRONIC MTLs DIV.,THE DEXTER CORP.

Address:211 FRANKLIN ST.

City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Info Phone

Num:716-372-6300

Emergency Phone Num:716-372-6309

Preparer's Name:JAMES P. HORNBURG

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK RD.

Box:City:SOMERVILLE

State:NJ

ZIP:08876

Country:US

Phone:908-218-9000

CAGE:7B953

===== Composition/Information on Ingredient

ts =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 30-60%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-B  
UTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10-30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACRYLIC RESIN

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL RAT LD50 IS NOT KNOWN

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Heal

th Hazards Acute and Chronic:PRODUCT IS IRRITATING TO BODY TISSUES.  
ITMAY EFFECT THE CENTRAL NERVOUS SYSTEM. POSSIBLE CHRONIC EFFECTS  
ARE "PAINTERS" SYNDROME.

Explanation of Carcinogenicity:THE PRODUCT CONTAINS NO INGREDIENT THAT  
IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE:IRRITATION SKIN:DRYING,IRRITATION,  
POSSIBLE DERMITIS WITH PROPLONGED/REPEATED CONTACT  
INHALED:NARCOSIS,RESPIRATORY IRRITATION INGESTED:G/I  
IRRITATION/DISTRESS,POSSIBL  
E NAUSEA,VOMITING.

Medical Cond Aggravated by Exposure:NONE GIVEN BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH  
SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE  
REUSE. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF  
NECESSARY. INGESTED:D O NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES  
OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY  
MOUTH I  
F UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A  
DOCTOR.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:52.0F,11.1C

Lower Limits:1.8

Upper Limits:10.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual F

ire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY  
TRAVEL ALONG GROUND OR FLOOR, THEN 'FLASH BACK' FROM A DISTANT  
IGNITION SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. MOP, WIPE UP,  
ADSORB WITH INERT MATERIAL. STORE AS A FLAMMABLE WASTE.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY AREA. KE

EP AWAY  
FROM ALL IGNITION SLURCES.

Other Precautions:NONE

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR RESPIRATOR FOR ORGANIC VAPOR IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE.

Ventilation:NORMAL ROOM VENTILATION IS SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED

. MFR RECOMMENDS LOCAL EXHAS

Protective Gloves:RUBBER, VINYL OR OTHER IMPERVIOUS

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE WASH STATION. IMPERVIOUS APRON AND BOOTS IF CONTACT IS LIKELY.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.

Supplemental Safety and Health

MSDS REVISION 02. PRODUCT CODE PO0012.

=====  
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P

. Text:180F,82C

Vapor Pres:78 MM

Vapor Density:4.5

Spec Gravity:0.94

Evaporation Rate & Reference:5.7 (BUTYL ACETATE = 1)

Solubility in Water:3-5%

Appearance and Odor:LIGHT AMBER LOW VISCOSITY LIQUID, AROMATIC ODOR

Percent Volatiles by Volume:55

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS,CHLORINATED HYDROCARBONS +  
ALKALIS,AMINES,AMMONIA,INORGANIC ACIDS,ISOCYANATES

Stability Condition to Avoid:HI

GH TEMPERATURES, SPARKS, AND OPEN FLAMES  
Hazardous Decomposition Products: CARBON DIOXIDE, CARBON  
MONOXIDE, N-BUTYLMETHACRYLATE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL  
REGULATIONS. MANUFACTURER MAKES NO SUGGESTION ABOUT DISPOSAL.  
DGSC-SSH SUGGESTS INCINERATION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the  
Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.