

HENTZEN COATINGS INC -- ID 08618 TUA-GD, SAND ZENTHANE -- 8010-01-234-2936

=====
Product Identification
=====

Product ID:ID 08618 TUA-GD, SAND ZENTHANE

MSDS Date:02/19/1990

FSC:8010

NIIN:01-234-2936

MSDS Number: BHXGN

=== Responsible Party ===

Company Name:HENTZEN COATINGS INC

Address:6937 W MILL ROAD

Box:18642

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Info Phone Num:414-353-4200

Emergency Pho

ne Num:414-353-4200 NIGHT: 800-424-9300

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOAMYL KETONE

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 30.79%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

Ingred Name:PREPOLYMER OF HEXAMETHYLENE

DIISOCYANATE
Fraction by Wt: 30-40%

Ingred Name:YELLOW IRON OXIDE PIGMENT
CAS:51274-00-1
Fraction by Wt: 1.0-5.0%
Other REC Limits:NUISANCE DUST

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 5-10%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 20-30%
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200
000
Fraction by Wt: 1.64%
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 1.26%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:1,6-DIISOCYANATOHXANE (HEXAMETHYLENE DIISOCYANATE)
CAS:822-06-0
RTECS #:MO1740000
Fraction by Wt: 120F OR < 32F. STORE LRG
AMTS IN BLDG DESIGNED TO COMPLY W/OSHA1910.106.KEEP AWAY FROM

SPARKS, OPEN FLAME.KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:IF MOISTURE ENTERS CONTAINERS, PRESSURE CAN BUILD DUE
TO REACTION, PRODUCE CO2, CAN CAUSE SEALED CONTAINER TO PRESSURIZE
& BURST. DO NOT RESEAL IF CONTAMINATED. DO NOT TAKE INTERNALLY.
CONTAINERS SHOULD BE GROUNDED WHEN POURING. ****

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SURGEON GENERAL REQUIRES AIRLINE RESPIRATORS TO
BE USED UNLESS AIR SAMPLING SHOWS EX
POSURE TO BE BELOW OSHA LIMITS.

THEN USE EITHER CHEM CARTRIDGE/AIRLINE RSPRTRS REQUIRED. USE SAME
PRECAUTIONS DURING MIXING OR WHERE PAINT FUMES ARE PRESENT

Ventilation:GEN DILUTION/LOCAL EXHAUST VENT IN VOL/PATTERN TO KEEP AIR
CONTAM CONCENT BELOW LIMITS.REMOVE DECOMP PROD WHEN WELD, ETC

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARDS/SHIELDS

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO KEEP SKIN
CONTACT AT MINIMUM. AVOID CONT
ACT WITH EYES, SKIN & CLOTHING. WASH
THOROUGHLY.

Work Hygienic Practices:WASH HANDS & ANY EXPOSED SKIN THOROUGHLY BEFORE
EATING OR SMOKING. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

**** AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. USE
W/ADEQUATE VENTILATION & RESPIRATORY EQUIP. EMPTIED CONTAINERS MAY
RETAIN HAZARDOUS RESIDUE OR EXPLOSIVE VAPORS. FOLLOW ALL
PRECAUTIONS IN THIS DATA SHEET UNTIL CONTAINER IS THOROUGHLY
CLEANED OR DESTROYED.**FLUSH
AREA W/WATER.REMOVE CONTAINER TO SAFE
PLACE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:244 TO 418F

Decomp Temp:Decomp Text:400F,204C

Vapor Pres:8.00

Vapor Density:> THAN AIR

Spec Gravity:1.23

Viscosity:65-68 KREBS

Evaporation Rate & Reference:EQUAL TO BUTYL ACETATE

Solubility in Water:REACTS WITH WATER

Appearance and Odor:OPAQUE LIQUID WITH SOLVENT ODOR.

Percent Volatiles by Volume:51.28

===== Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid: YES

WATER, ALCOHOLS, GLYCOL ETHERS, AMINES.

Stability Condition to Avoid: WATER CONTAMINATION. *(CO₂ EVOLVED). DON'T APPLY TO HOT SURFACES. NEVER USE WELD/CUT TORCH ON/NEAR DRUM (EVEN EMPTY DRUM)

Hazardous Decomposition Products: BY FIRE: CO₂, CO, OXIDES OF NITROGEN, TRACES OF HYDROGEN CYANIDE, HEXAMETHYLENE DIISOCYANATE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN A

CCORDANCE WITH LOCAL, STATE &

FEDERAL REGULATIONS. INCINERATION IS PREFERRED METHOD OF DISPOSAL. ***CARBIDE'S TERGITOL TMN-10 (20%) & WATER

(80%). **W/NON-SPARK TOOLS INTO OPEN CONTAINER- ADD MORE NEUTRALIZER & WASH AREA W/NEUTRALIZER **

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this

information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.