View NSN Online: https://aerobasegroup.co.il/nsn/6520-00-782-0520

## KERR MANUFACTURING COMPANY -- FORMATRAY LIQUID -- 6520-00-782-0520

Product ID:FORMATRAY LIQUID

MSDS Date:04/25/1989

FSC:6520

NIIN:00-782-0520

MSDS Number: BJCQS === Responsible Party ===

Company Name: KERR MANUFACTURING COMPANY

Address:28200 WICK ROAD

City:ROMULUS

State:MI ZIP:48174

Info Phone Num:(313) 946-7800

Emergency Phone Num: (313) 946-7800

CAGE:EO529

===

Contractor Identification ===
Company Name: KERR CORP

Address:1717 W COLLINS AVENUE

Box:City:ORANGE

State:CA

ZIP:92867-5422 Country:US

Phone:800-537-7187

CAGE:33339

Company Name: KERR MANUFACTURING COMPANY, DIVISION OF SYBRON COR

Address:28200 WICK ROAD

Box:City:ROMULUS

State:MI ZIP:48174 Country:US

Phone: (313) 946-7800

CAGE:EO529

====== Composition/Information on Ingredients ========

Ingred Name: METHYL METHACRYLATE (SARA III)

CAS:80-62-6

RTECS #:OZ5075000 Fraction by Wt: 99%

Oth

er REC Limits:100 PPM **OSHA PEL:100 PPM** ACGIH TLV:100 PPM; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: RASHES. INHALATION: HEADACHES, NAUSEA, DROWSINESS, & UNCONSCIOUSNESS. INGESTION: GASTRO-INTESTINAL DISTRESS. **Explanation of Carcinogenicity:NONE** Effe cts of Overexposure:EYES: IRRITATION. SKIN: RASHES. INHALATION: HEADACHES, NAUSEA, DROWSINESS, & UNCONSCIOUSNESS. INGESTION: GASTRO-INTESTINAL DISTRESS. Medical Cond Aggravated by Exposure: RASHES First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN OR GIVE ARTIFICIAL RESPIRATION, AS REQUIRED. INGESTION: CALL PHYSICIAN. \_\_\_\_\_\_ Fire Fighting Measures ========= Flash Point:50F Lower Limits: 1.7% Upper Limits:8.2% Extinguishing Media: CO2, FOAM, DRY CHEMICALS, WATER FOG Fire Fighting Procedures: FIGHT FIRES FROM SAFE DISTANCE. COOL EXPOSED MATERIAL W/COLD WATER SPRAY.

Unusual Fire/Explosion Hazard: SEALED CONTAINERS EXPOSED TO ELEVATED

TEMPERATURES MAY RUPTURE EXPLOSIVELY DUE TO POLYMERIZATION. VAPORS ARE >AIR & MAY TRAVEL.

======== Accidental Release Measures ============

Spill

Release Procedures: EVACUATE AREA, ELIMINATE IGNITION SOURCES.	
ABSORB SPILLS W/INERT MATERIAL & TRANSFER TO SUITABLE CONTAINER F	OR
DISPOSAL.	

Handling and Storage Precautions:STORE IN A COOL, DARK PLACE. KEEP AWAY FROM IGNITION SOURCES.

Other Precautions:USE ACCORDING TO DIRECTIONS. USE GOOD PERSONAL HYGIENE.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WHEN VAPORS EXCEED TLV, SELF-CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP