

EVERSEAL MFG CO INC -- YELLOW GLOSS ALKYD ENAMEL, 13655 -- 8010-00-598-5945
===== Product Identification =====

Product ID:YELLOW GLOSS ALKYD ENAMEL, 13655
MSDS Date:05/27/1987
FSC:8010
NIIN:00-598-5945
MSDS Number: BJLHY
=== Responsible Party ===
Company Name:EVERSEAL MFG CO INC
Address:475 BROAD AVE
City:RIDGFIELD
State:NJ
ZIP:07657-2329
Country:US
Info Phone Num:201-943-4986 / FAX 201-943-1123

Emergency Phone Num:201-943-4986
CAGE:72988
=== Contractor Identification ===
Company Name:EVERSEAL MFG CO INC
Address:475 BROAD AVE
Box:City:RIDGFIELD
State:NJ
ZIP:07657-2329
Country:US
Phone:201-943-4986
CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN
Fraction by Wt: 30%
Other REC Limits:NONE SPECIFIED

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
AC

GIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:LEAD CHROMATE - AS PB
CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: 18%
Other REC Limits:NONE SPECIFIED
OSHA PEL:AS DUST

Ingred Name:LEAD CHROMATE - AS CR
CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.5 MG/M3

Ingred Name:MINERAL SPIRITS (VP 5) (TOXICITY DATA: 5 G/KG ORAL)
CAS:64742-86-5
RTECS #:LX3296500
Fraction by Wt: 38%
Other REC Limits:NONE SPECIFIED
OSHA PEL:120 PPM

=====
===== Hazards

Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION: DIZZINESS, NAUSEA,
POSSIBLE UNCONSCIOUSNESS. IRRITATING TO SKIN AND EYES: FREQUENT AND
PROLONGED EXPOSURE TO LEAD CHROMATE DUST CAN CAUSE LIVER AND/OR
KIDNEY DAMAGE. SANDING, GRINDING, BLA STING OR WELDING OPERATIONS
SHOULD BE PERFORMED ONLY IF ADEQUATE PRECAUTIONS ARE TAKEN.

Explanation of Carcinogenicity:CHROMATES ARE CARCINOGENS.

Effects

of Overexposure:INHALATION: DIZZINESS, NAUSEA, POSSIBLE
UNCONSCIOUSNESS. IRRITATING TO SKIN AND EYES: FREQUENT AND
PROLONGED EXPOSURE TO LEAD CHROMATE DUST CAN CAUSE LIVER AND/OR
KIDNEY DAMAGE. SANDING, GRINDING, BLA STING OR WELDING OPERATIONS
SHOULD BE PERFORMED ONLY IF ADEQUATE PRECAUTIONS ARE TAKEN.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION
IF NEEDED. SKIN: WASH WITH SOAP

AND WATER. EYES: FLUSH WITH WATER.
CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:105 F/41 C
Lower Limits:1
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING MEDIA.

===== Accidental Release Measures =====

Spill Release Procedures:ENSURE ADEQUATE VENTILATION. R
REMOVE IGNITION
SOURCES. ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE
SPARK-PROOF SCOOP FOR LARGER SPILLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT OR OPEN IGNITION
SOURCES.
Other Precautions:NPCA/HMIS RATING 3,2,0,H

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME AND DUST MASK OR AIR-SUPPLIED HOOD
Ventilation:ADEQUATE TO ENSURE LEL NOT ACHIEVED
P
rotective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:323 TO 390F
Vapor Density:> THAN AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXI

DIZING MATERIAL

Hazardous Decomposition Products: CARBON MONOXIDE AND/OR CARBON DIOXIDE
ON COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF AS PER LOCAL AND FEDERAL REGULATIONS
FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.