View NSN Online: https://aerobasegroup.co.il/nsn/8010-00-935-7065

Product ID:LACQUER, ACRYLIC, ORANGE 12197, ID 794297

MSDS Date:09/12/1990

FSC:8010

NIIN:00-935-7065

MSDS Number: BJLKP

=== Responsible Party ===

Company Name: PRATT & LAMBERT INC

Box:2153 City:WICHITA

State:KS ZIP:67201 Country:US

Info Phone Num:316-733-1361

Emergency Phone Num

:316-733-1361 CAGE:PRATT

=== Contractor Identification ===

Company Name: PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY ZIP:11710 Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

====== Composition/Information on Ingredients ========

Ingred Name: CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000 Fraction by Wt: 20% Other REC Limi ts:LFL 1.1

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 20%

Other REC Limits:LFL 2.0/UFL 10.0 OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: BUTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000 Fraction by Wt: < 5% Other REC Limits:LFL .3 EPA Rpt Qty:100 LBS

DOT Rpt Qty: 100 LBS

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000 Fraction by Wt: 5%

Other REC Limits:LFL 3.0/UFL 13.0 OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 10%

Other REC Limits:LFL 1.7.UFL 7.1 OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: LEAD CHROMATE (OSHA-CEIL .1000 MG/CU.M.) (SARA 313

REPORTABLE) CAS:7758-97-6 RTECS # :GB2975000

Fraction by Wt: 15%

Other REC Limits: NONE SPECIFIED

OSHA PEL:.0500 MG/CU.M. ACGIH TLV:.0500 MG/CU.M.

Ingred Name:LEAD SULFATE (SARA III)

CAS:7446-14-2

RTECS #:OG4375000 Fraction by Wt: 5%

Other REC Limits: NONE SPECIFIED

OSHA PEL:SEE 1910.1025

ACGIH TLV:0.15 MG PB/M3; 9192

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name: MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000 Fraction by Wt: < 1%

Other REC Limits: NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Ingred Name:VOC

5.10 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS 612 G/L LESS WATER

RTECS #:9999999VO

Other REC Limits: NONE SPECIFIED

Ingred Name: VOC 17.81 LB/GAL SOLIDS 2137 G/L SOLIDS

RTECS #:9999999VO

Other REC Limits: NONE SPECIFIED

========== Hazards Identification ================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING MAY CAUSE GASTROINTESTI
NAL

IRRITATION & CHEMICAL PNEUMONITIS. MAY SEVERELY IRRITATE NOSE, THROAT, EYES & SKIN. OTHER EFFECTS: DAMAGE TO BLOOD FORMING, KIDNEYS, URINE, REPRODUCTIVE SYSTEM, B RAIN, & NERVOUS SYSTEM. DELIBERATELY CONCENTRATING/INHALING CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS INGREDIENTS WHICH ARE LISTED AS POTENTIAL CARCINOGENS BY THE IARC & THE NTP. Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, VOMITING, CONFUSION, LOSS O

F APPETITE, METALLIC TASTE IN MOUTH, ANXIETY,
CONSTIPATION, WEAKNESS, INSOMNIA, MUSCLE & JOINT PAIN, FINE
TREMORS, NUMBNESS, HYPERACTIVITY, COL IC, & SEVERE IRRITATION
REACTION IF PRODUCT IS SWALLOWED, INHALED, ABSORBED THROUGH SKIN,
OR GETS INTO EYES.

Medical Cond Aggravated by Exposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. PREXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO LEAD.

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR IMMEDIATELY. IF BREATHING STOPPED, GIVE CPR & KEEP WARM. EYE: FLUSH WITH LARGE AMOUNTS OF WA TER FOR 15 MINUTES LIFTING UPPER/LOWER LIDS CONTINUOUSLY. SKIN: REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP & WATER. GET MEDICAL ATTENTION IMMEDIATELY FOR ANY OF THESE C ONDITIONS.

========== Fire Fighting Measures ===============

Flash Point:24F/-4C

Lower Limits:SEE INGRED Upper Limits:SEE INGRED

Extinguishing Media: USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILDUP & POSSIBLE AUTO-IGNITE EXPLOSION. USE FOG NOZZLES WITH WATER.

Unusual Fire/Explosi

on Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE
TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY
NOT BE IMMED APPARENT. OBTAIN MEDICAL ATTENTION.

======== Accidental Release Measures ===========

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO COVERED METAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARKING TOOLS. PREVENT CONTAMINATION OF S EWERS, STREAMS, &

GROUNDWATER.
============== Handling and Storage ===============
Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106. Other Precautions:NEVER WASH OR REUSE EMPTY CONTAINERS FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE, CUT OR USE PRESSURE TO EMPTY CONTAINERS. DISPOSE AS HAZARDOUS W ASTE, IGNITABLE D001, EP TOXIC D008.
======================================
Respiratory Protection:IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED CHEM CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN CONFINED AREAS USE A NIOSH /MSHA APPROVED AIR SUPPLIED RESPIRATOR. Ventilation:DILUTE & LOCAL EXHAUST RECOMMENDED TO CONTROL CONCENTRATE OF HAZARDOUS INGREDIENTS.** Protective Gloves:WEAR SOLVENT IMPERMEABLE GLOVES.
Eye Protection:W EAR SAFETY SPECTACLES. Work Hygienic Practices:DO NOT TAKE INTERNALLY. PREVENT SKIN CONTACT. WASH HANDS & FACE BEFORE EATING OR DRINKING. KEEP AWAY FROM
CHILDREN. Supplemental Safety and Health ** REMOVE DECOMPOSITION PRODUCTS THAT ARE GENERATED WHEN WELDING, CUTTING, OR BRAZING OBJECTS COATED WITH THIS PRODUCT. THIS PRODUCT CONTAINS LEAD, WHICH, IF PRESENT IN WASTE AT 5.0 MG/1 OR MORE AFTER BEING EXTRACTED, IS CONSIDERED EP TOXIC & A HAZARDOUS WASTE UNDER RCRA REGULATIO NS. HAZARDOUS WASTE NO. WOULD BE D008.
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:175 TO 312F Vapor Density:> THAN AIR

Evaporation Rate & Description Rate & Reference: SLOWER THAN ETHER

======== Stability and Reactivity Data =========

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF

Percent Volatiles by Volume:71

IGNÍTION.

Hazar

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

- dous Decomposition Products:BURNING, HEAT BY WELDING/CUTTING, PRODUCES SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF CHROMIUM & LEAD.
- Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN I/A/W FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISP OF FLAMMABLE M ATERIALS.

CONTAMINATED ABSOR BENT MAY BE DISPOSED IN A HAZARD WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume

responsibility for the suitability of this information to their particular situation.