

UNION OIL CO OF CALIFORNIA UNION CHEMICALS DIV -- PERCHLOROETHYLENE --
6810-00-819-1128

===== Product Identification =====

Product ID:PERCHLOROETHYLENE

MSDS Date:01/25/1990

FSC:6810

NIIN:00-819-1128

MSDS Number: BJMFD

=== Responsible Party ===

Company Name:UNION OIL CO OF CALIFORNIA UNION CHEMICALS DIV

Address:1900 E GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60194-5021

Country:US

Info Phone Num:80

0-438-2968

Emergency Phone Num:800-424-9300 CHEMTRC OR800-356-3129

CAGE:DO716

=== Contractor Identification ===

Company Name:UNION OIL CO OF CALIF;UNION CHEMICAL DIV

Address:1345 NORTH MEACHAM ROAD

City:SCHAUMBURG

State:IL

ZIP:60196

Country:US

Phone:312-885-5450

CAGE:DO716

Company Name:UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA

Address:1345 N MEACHAM

Box:City:SCHAUMBURG

State:IL

ZIP:60196

Phone:312-490-2500/800-424-9300(CHEMTREC)

CAGE:94684

===== Composition/Information on Ingredient

ts =====

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)
CAS:127-18-4
RTECS #:KX3850000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:25PPM/100,A3 STEL;94
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 5000 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazard
s Acute and Chronic:ACUTE: MAY CAUSE EYE & SKIN
IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CENTRAL NERVOUS
SYSTEM DEPRESSANT. LOSS OF CONSCIOUSNESS AND EVEN DEATH CAN OCCUR
AT HIGH LEVELS OF EXPOSURE. CHRONIC:LI VER AND KIDNEY DAMAGE.
ASPIRATION HAZARD DO NOT INDUCE VOMITING. PROBABLE CANCER HAZARD.
Explanation of Carcinogenicity:LISTED AS A CARCINOGEN BY NTP AND IARC.
Effects of Overexposure:INCOORDINATION AND IMPAIRED JUDGMENT MAY OCCUR
AT VAPOR EXPOSURES FROM 500-
1000 PPM. DIZZINESS, DROWSINESS, AND
GENERAL ANESTHETIC EFFECTS MAY OCCUR IN RANGES OF 1000 PPM AND
HIGHER.
Medical Cond Aggravated by Exposure:EYE/SKIN/RESPIRATORY CONDITIONS MAY
BE AGGRAVATED BY EXPOSURE. MAY CAUSE CANCER.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR.
IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYE:
FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR
15 MINUTES. GET
MEDICAL AT TENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH
SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING. GIVE
MILK OR USP MINERAL OIL. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE

WATER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS INCLUDING PHOSGENE AND HYDROGEN CHLORIDE.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE UP WITH RAGS OR TOWELS.
LARGE SPILLS: WEAR NIOSH APPROVED RESPIRATOR. VENTILATE AREA. DIKE TO RETAIN FLUID. PUMP UP FREE LIQUID. RESIDUE WILL EVAPORATE QUI
CKLY. DO NOT FLUSH TO SEWER OR WATERWAY.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE. KEEP CONTAINERS CLOSED WHEN NOT IN USE.
Other Precautions:DO NOT USE WITH PRESSURIZED ALUMINUM SYSTEMS. READ AND FOLLOW DIRECTIONS ON LABEL. DO NOT REUSE CONTAINERS. AVOID WELDING, BRAZING, DRILLING, SOLDERING AND OTHER HIGH TEMPERATURE AND SPARK CONDITIONS AROUND THIS PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN HIGH VAPOR AREA, USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. USE SELF-CONTAINED BREATHING APPARATUS IF ALLOWABLE VAPOR LEVELS ARE EXCEEDED.
Ventilation:LOCAL EXHAUST RECOMMENDED TO CONTROL VAPORS BELOW 50% OF TLV.
Protective Gloves:NEOPRENE, PVA GLOVES RECOMMENDED.
Eye Protection:USE CHEMICAL SAFETY GOGGLES.
Other Protective Equipment:APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE. EYE WASH STATION & SAFETY SHOWER RECOMMENDED.
Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING, SMOKING OR USING TOILET FACILITIES. DO NOT BREATHE VAPORS OR MIST.
Supplemental Safety and Health
TARGET ORGANS ARE SKIN, CNS, CVS, AND EYES. STORE IN COOL, DRY PLACE.

===== Physical/Chemical Properties =====

HCC:T4
Boiling Pt:B.P. Text:250F,121C
Vapor Pres:14
Vapo

r Density:5.8 AIR=1

Spec Gravity:1.620

Evaporation Rate & Reference:2.10 (N-BUTYL ACETATE=1)

Solubility in Water: