

FIBER-RESIN CORPORATION -- FR-7035 FILM ADHESIVE -- 8040-00-116-1437

=====  
Product Identification  
=====

Product ID:FR-7035 FILM ADHESIVE

MSDS Date:07/10/1990

FSC:8040

NIIN:00-116-1437

MSDS Number: BJPXC

=== Responsible Party ===

Company Name:FIBER-RESIN CORPORATION

Address:170 W. PROVIDENCIA AVE

City:BURBANK

State:CA

ZIP:91502

Country:US

Info Phone Num:800-424-9300

Emergency Phone Num:800-424-9300

0

Preparer's Name:SAM ENGEL, SR.

CAGE:DO271

=== Contractor Identification ===

Company Name:3H B FULLER CO

Box:City:BURBANK

State:CA

ZIP:91503

Country:US

Phone:800-624-9487;612-481-3300

CAGE:0HB93

Company Name:FIBER-RESIN CORP.

Address:170 W PROVIDENCIA AVE

Box:91503

City:BURBANK

Phone:800-424-9300

CAGE:DO271

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER RESIN

CAS:25068-38-6

RTECS #:KD4380000

Fraction by Wt: 10-20%

Other REC Limits

:NONE SPECIFIED

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER-RESIN

CAS:25036-25-3

Fraction by Wt: 13-30%

Other REC Limits:NONE SPECIFIED

Ingred Name:CARBOXY TERMINATED BUTYL NITRILE (ACRYLONITRILE BUTADIENE RESIN)

CAS:68891-50-9

Fraction by Wt: 3-6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NONE

ACGIH TLV:NONE

Ingred Name:ACRYLONITRILE (SARA III)

CAS:107-13-1

RTECS #:AT5250000

Fraction by Wt: 1-3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE 1910.1045

ACGIH TLV:S, 2 PPM;A2 9394

EPA Rpt Qty:10

0 LBS

DOT Rpt Qty:100 LBS

Ingred Name:RESORCINOL DIGLYCIDYL ETHER

CAS:101-90-6

RTECS #:VH1050000

Fraction by Wt: 0.5-1%

Other REC Limits:NONE SPECIFIED

Ingred Name:POLYAMIDE RESIN

CAS:68989-76-4

Fraction by Wt: 0.5-2%

Other REC Limits:NONE SPECIFIED

Ingred Name:MODIFIED TERTIARY AMINE

CAS:51365-20-9

RTECS #:NM1275000

Fraction by Wt: 490F,>254C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY.

Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Expl

osion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY  
BE TOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER SPILLED MATERIAL AND PLACE IN SUITABLE  
CONTAINER FOR REUSE OR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT 40F OR BELOW.  
Other Precautions:MATERIAL IS NON-HAZARDOUS.

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:NOT NORMALLY REQUIRED.

Ventilation:MECHANICAL.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH FOUNTAIN, SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Solubility in Water:INSOLUBLE

Appearance and Odor:CREAM COLORED, TACKY FILM SLIGHT ODOR

Percent Volatiles by Volume: