View NSN Online: https://aerobasegroup.com/nsn/8040-00-433-4065

## BAKER SEALANTS & COATINGS CO. -- ADHESIVE -- 8040-00-433-4065

============= Product Identification ==============

Product ID:ADHESIVE MSDS Date:01/01/1987

FSC:8040

NIIN:00-433-4065

MSDS Number: BJQBW === Responsible Party ===

Company Name: BAKER SEALANTS & COATINGS CO.

Address:234 SUYDAM AVENUE

Box:B

City: JERSEY CITY

State:NJ ZIP:07304 Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-6986

CAGE:FO

833

=== Contractor Identification ===

Company Name: BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City: JERSEY CITY

State:NJ

ZIP:07304-3306

Phone: (201) 333-6986

CAGE:FO833

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name: STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US


Phone:201-437-6501

CAGE:33150

====== Comp

osition/Information on Ingredients ======== Ingred Name:SOLVENTS CAS:64742-86-5 RTECS #:LX3296500 Fraction by Wt: 70% Other REC Limits: NONE SPECIFIED ACGIH TLV:100 PPM Ingred Name: POLYMERS Fraction by Wt: 30% Other REC Limits: NONE SPECIFIED Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 6% Other REC Limits: NONE SPECIFIED OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 24% Other REC Limits: NONE SPECIFIED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS ========== Hazards Identification ================ Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure: ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS, IMPAIRMENT OF COORDINATION.

Firs



aporation Rate & Department of the Robert Solubility in Water: INSOLUBLE
Appearance and Odor: CREAM COLORED LIQUID Percent Volatiles by Volume: 75

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:FIRE, SPARKS, OPEN FLAME, EXCESSIVE HEAT Hazardous Decomposition Products:COMBUSTION PRODUCTS OF SOLVENT AND RESIN UNKNOWN HYDROCARBONS.

==		Disposal	Considerat	tion
S	=======================================	:=		

Waste Disposal Methods: IN ACCORDANCE WITH FEDERAL AND/OR STATE REGULATION COVERING SOLID WASTE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.