View NSN Online: https://aerobasegroup.com/nsn/7930-00-901-2088

HYSAN CORPORATION -- AA-40A GLASS CLEANER LIQUID TYPE II -- 7930-00-901-2088

======== Product Identification ============

Product ID:AA-40A GLASS CLEANER LIQUID TYPE II

MSDS Date:10/27/1986

FSC:7930

NIIN:00-901-2088

MSDS Number: BJWBL === Responsible Party ===

Company Name: HYSAN CORPORATION

Address:4309 S. MORGAN ST.

City:CHICAGO

State:IL ZIP:60609

Info Phone Num:(312) 376-8981 Emergency Phone Num:(312) 52

3-1010

CAGE:HYSAN

=== Contractor Identification ===

Company Name: HYSAN CORP (BOUGHT BY HYSAN/AMP-NONE IN CHICAGO)

Address:919 W 38TH ST

Box:City:CHICAGO

State:IL

ZIP:60609-1419

Country:US

Phone:NONE

CAGE:27689

Company Name: HYSAN CORPORATION

Address:2929 ALLEN PARKWAY, SUITE 2130

City:HOUSTON

State:TX ZIP:77019 Country:US

Phone:713-620-7740

CAGE:HYSAN

====== Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Frac

ACGIH TLV:400 PPM/500STEL;9192 ============= Hazards Identification ======================== Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: PAIN & IRRITATION. INGESTION: HARMFUL & GASTROINTESTINAL DISCOMFORT. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: EYES: PAIN & IRRITATION. INGESTION: HARMFUL & ASTROINTESTINAL DISCOMFORT. First Aid:EYES: FLUSH W/WATER. INGESTION: GIVE WATER OR MILK. OBTAIN MEDICAL ATTENTION. ============= Fire Fighting Measures ======================== Flash Point Method:TCC Flash Point:>200F Extinguishing Media:WATER Fire Fighting Procedures: AS REQUIRED ======== Accidental Release Measures =========== Spill Release Procedures:WIPE UP SPILLS. _____ Handling and Storage ========== Handling and Storage Precautions: STORE IN DRY, COOL AREA. KEEP OUT OF REACH OF CHILDREN. READ ENTIRE LABEL BEFORE USING. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: AS REQUIRED Ventilation: PROVIDE ADEQUATE MECHANICAL VENTILATION TO KEEP 32F Vapor Pres:18 Vapor Density:

tion by Wt: 1-5%

Other REC Limits:400 PPM OSHA PEL:400 PPM/500 STEL