View NSN Online: https://aerobasegroup.com/nsn/6810-00-062-6954

PHIPPS PRODUCTS CORP(MFG-TENNESSEE EASTMAN CO) -- ETHYL ACETATE

6810-00-062-6954

============= Product Identification =================

Product ID:ETHYL ACETATE

MSDS Date:01/01/1985

FSC:6810

NIIN:00-062-6954

MSDS Number: BJXFM === Responsible Party ===

Company Name: PHIPPS PRODUCTS CORP(MFG-TENNESSEE EASTMAN CO)

Address: EASTMAN RD

Box:511

City:KINGSPORT

State:TN ZIP:37662 Country:US

Emergency Phone Num:NONE

Prepar

er's Name: NOT PROVIDED

CAGE:1P058

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV

Address: EASTMAN RD

Box:511

City:KINGSPORT

State:TN ZIP:37662 Country:US

Phone:615-229-2000

CAGE:7B604

Company Name: PHIPPS PRODUCTS CORP.

Box:511 City:BOSTON State:MA

Country:US

Phone:517-636-4400

CAGE:1P058

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000 OSHA PEL:400 PPM ACGIH TLV:400

============= Hazards Identification ======================== Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NONE. Effects of Overexposure: EYES-IRRITATION, SKIN-PROLONGED CONTACT DRIES & CRACKS. VAPOR IRRITATES MUCOUS MEMBRANES, NARCOTIC EFF. First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES.CALL DOCTOR.SKIN-FLUSH WITH WATER INHALATION-REMOVE TO FRESH AIR. =========== Fire Fighting Measures ========================== Flash Point Method:TCC Flash Point:=-4.4C, 24.F Lower Limits:2.02 Upper Limits:11.5 Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE Spill Release Procedures: CONTAIN SPILL, IF SMALL FLUSH WITH LARGE VOLUME OF WATER.REMOVE ANY SOURCE OF SPARKS OF FL AME.PROVIDE ADEQUATE EXHAUST.ABSORB MATERIAL ============= Handling and Storage ========================== Handling and Storage Precautions: AVOID EYE CONTACT. AVOID REPEATED OR PROLONGED SKIN CONTACT.USE WITH ADEQUATE VENTILATION TO KEEP BELOW TLV.KEEP CONTAINER CLOSED Other Precautions:NONE ====== Exposure Controls/Personal Protection ======== Respiratory Protection: SELF CONTAINED IF NEEDED, ESPECIALLY IN CONFINED **AREAS** Ventilation:LOCAL - RECOMMENDED **Prote**

PPM; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Supplemental Safety and Health
========= Physical/Chemical Properties =========
HCC:F2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=71.7C, 161.F Vapor Pres:75 Spec Gravity:0.8845 Evaporation Rate & Deference:4.2,BUTYL ACETATE Solubility in Water:7.4% Appearance and Odor:CLEAN VOLATILE LIQUID,CHARACTERISTIC,NON RESIDUAL Percent Volatiles by Volume:100
======================================
Stability Indicator/Materials to Avoid:YES OXIDIZERS

ctive Gloves:RUBBER

Eve Protection: FACE SHIELD/SAFETY GOGGLE

Waste Disposal Methods:PLACE ABSORBED MATERIAL IN CONTAINERS SUITABLE FOR SHIPPING TO DISPOSAL AREA

======= Disposal Considerations ===========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.