View NSN Online: https://aerobasegroup.co.il/nsn/6750-00-155-6956

CLAYTON CHEMICAL CO. -- SUPERCHEM 225 HC FIXER -- 6750-00-155-6956

Product ID:SUPERCHEM 225 HC FIXER MSDS Date:01/06/1988 FSC:6750 NIIN:00-155-6956 MSDS Number: BJYRV === Responsible Party === Company Name: CLAYTON CHEMICAL CO. Address:13310 FIGUEROA STREET **City:LOS ANGELES** State:CA ZIP:90061 Country:US Info Phone Num:213-538-9530 Emergency Phone Num:213-538-95 30 CAGE:61803 === Contractor Identification === Company Name: CLAYTON CHEMICAL CO. Address:13310 S. FIGUEROA STREET Box:City:LOS ANGELES State:CA ZIP:90061 Country:US Phone:310-538-9530/800-424-9300(CHEMTREC) CAGE:61803

Ingred Name:ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 12% Other REC Limits:NONE SPECIFIED OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

==

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT ESTABLISHED. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION:IRRITATION, PULMONARY EDEMA, AND CHEMICAL PNEUMONITIS. EYES:IRRITATION/BURNS. SKIN:IRRITATION. VAPORS MAY CAUSE MUCOUS MEMBRANE IRRITATION. INGESTION: MAY CAUSE BURNS OF THE ESOPHAGUS AND S TOMACH, ABDOMINAL

PAIN.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure: IRRITATION OF EYES, SKIN, THROAT, COUGHING, CHEST PAIN AND BREATHING DIFFICULTY.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE SKIN, EYES AND LUNGS MAY BE AT INCREASED RISK FROM EXPOSURE.

First A

id:EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET IMMEDIATE MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING AND SHOES. WASH SKIN WITH SOAP AND WATER. GET MEDICA L ATTENTION. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IMMEDIATELY GIVE ONE GLASS OF MILK OR WATER. CALL A PHYSICIAN AT ONCE. NOTE: ALKALINE SOLUTION. TREAT ACCORDINGLY.

Flash Point Method:CC

Flash Point:>109F,>43C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

S

pill Release Procedures:NEUTRALIZE WITH SODIUM BISULFATE. WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBENT. PUT IN DISPOSAL CONTAINER. REMOVE RESIDUE WITH LARGE AMOUNTS OF WATER BY FLUSHING TO AN ACID-FREE SEWER. Neutralizing Agent:SODIUM BISULFATE

Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE AND AWAY FROM ACIDS. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. PROTECT CONTAINE

RS FROM DAMAGE.

Other Precautions: AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING. USE OF NON-ALKALINE TYPE HAND CLEANER REDUCES RISK OF ALLERGIC SKIN REACTION.

Respiratory Protection: AN APPROPRIATE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPOR SHOULD BE WORN IF NEEDED. Ventilation: MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

Protective Gloves: NEOPRENE OR NATURAL RUBBER

Eye Protection:SAFETY GO

GGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE.

================= Physical/Chemical Properties

HCC:C2 Boiling Pt:=100.C, 212.F Spec Gravity:1.15 pH:4.8 Evaporation Rate & amp; Reference: