

PERMATEX INDUSTRIAL CORP -- PLASTIC CLEANER 80183 -- 7930-00-935-3794

=====
Product Identification
=====

Product ID:PLASTIC CLEANER 80183

MSDS Date:03/30/1990

FSC:7930

NIIN:00-935-3794

MSDS Number: BJZGH

=== Responsible Party ===

Company Name:PERMATEX INDUSTRIAL CORP

Address:30 TOWER LANE

City:AVON

State:CT

ZIP:06001

Country:US

Info Phone Num:203-677-7727

Emergency Phone Num:203-677-7727

Prepar

er's Name:STEPHEN REPETTO

CAGE:DO527

=== Contractor Identification ===

Company Name:PERMATEX INDUSTRIAL CORP; LOCTITE CORP

Address:30 TOWER LANE; AVON PARK SOUTH

Box:11915

City:AVON

State:CT

ZIP:06001

Phone:203-677-7727

CAGE:DO527

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 65-70%

Other REC Limits:NONE SPECIFIED

Ingred Name:VM&P NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 20-25%

Other REC Li

imits:NONE SPECIFIED
OSHA PEL:300 PPM/1370 MG/M3
ACGIH TLV:300 PPM/1350 MG/M3

Ingred Name:CALCIUM CARBONATE
CAS:471-34-1
RTECS #:FF9335000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15MG/M3DUST/5MG/M3RE
ACGIH TLV:10 MG/M3 DUST

Ingred Name:POLY (DIMETHYLSILOXANE)
CAS:63148-62-9
Fraction by Wt: < 1%
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:LONG TERM EXPOSURE TO LIQUID MAY CAUSE
D
RYING AND CRACKING OF SKIN. NARCOSIS AT HIGH CONCENTRATION.
Effects of Overexposure:DIZZINESS, HEADACHE, NAUSEA. LONG TERM EXPOSURE
TO LIQUID MAY CAUSE DRYING AND CRACKING OF SKIN. NARCOSIS AT HIGH
CONCENTRATION.

=====
First Aid Measures
=====

First Aid:INGESTION:DO NOT INDUCE VOMITING. OBTAIN MEDICAL ATTENTION.
INHALATION:REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN MEDICAL
ATTENTION. SKIN CONTACT:FLUSH WITH SOAP AND WATER. EYE
CON
TACT:FLUSH WITH WATER AT LEAST 15 MINUTES AND OBTAIN MEDICAL
ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:80F/27C
Lower Limits:1
Upper Limits:12
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

=====
Accidental Release Measures
=====

Spill Release Procedures:SOAK UP IN ANY INERT ABSORBENT AND STORE IN A
CLOSED CONTAINER UNTIL DISPOSAL.

=====
Handling and Storage
=====

=====
Handling and Storage Precautions:STORE AWAY FROM HEAT OR FLAME. AVOID
PROLONGED BREATHING OF FUMES. AVOID PROLONGED SKIN CONTACT. DO NOT
USE NEAR HEAT OR FLAMES.

=====
Exposure Controls/Personal Protection

Ventilation:MUST BE ADEQUATE TO AVOID EXCEEDING TLV.
Protective Gloves:IMPERMEABLE GLOVES FOR PROLONGED USE.
Eye Protection:SAFETY GLASSES OR GOGGLES.
Supplemental Safety and Health

=====
Physical/Chemical Properties

HCC:F3
Vapor Density:4.7
Spec Gravity:0.99 @ 60F
pH:7
Solubility in Water:MISCIBLE
Appearance and Odor:WHITE CREAMY LIQUID, MILD PETROLEUM ODOR

=====
Stability and Reactivity Data

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:BY FIRE OR THERMAL DECOMP:IRRITATING
ORGANIC VAPORS.

=====
Disposal Considerations

Waste Disposal Methods:INCINERATE FOLLOWI
NG EPA AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this informati

on to their
particular situation.