

DOW CHEMICAL U.S.A., GOVERNMENT MARKETING -- EXT MAGNESIUM WELDING ROD AZ92A --
3439-00-204-3203

===== Product Identification =====

Product ID:EXT MAGNESIUM WELDING ROD AZ92A

MSDS Date:06/13/1990

FSC:3439

NIIN:00-204-3203

MSDS Number: BKHHT

=== Responsible Party ===

Company Name:DOW CHEMICAL U.S.A., GOVERNMENT MARKETING

Address:2020 DOW CENTER

City:MIDLAND

State:MI

ZIP:48640-6030

Country:US

Info

Phone Num:517-636-1000

Emergency Phone Num:517-636-4400

CAGE:96717

=== Contractor Identification ===

Company Name:AUFHAUSER CORP

Address:39 WEST MALL

Box:City:PLAINVIEW

State:NY

ZIP:11803-4209

Country:US

Phone:212-757-6824/FAX: 516-694-8690

CAGE:59401

Company Name:DOW CHEMICAL CO

Address:100 LARKIN CENTER

Box:City:MIDLAND

State:MI

ZIP:48674

Country:US

Phone:800-258-2436

CAGE:96717

Company Name:INWELD MFG CORP

Address:3962 PORTLAND ST

Box:40

City:COPLAY

State:PA

ZIP:18037-0040

Country:US

Phone:61

0-261-1900
CAGE:66376

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM (SARA III)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 9.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15MG/M3 DUST/5 FUME
ACGIH TLV:10MG/M3 DUST; 9293

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 2.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG ZNO/M3
ACGIH TLV:10 MG ZNO/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MANGANES
E (SARA III)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 0.15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:MAGNESIUM
CAS:7439-95-4
RTECS #:OM2100000
Fraction by Wt: BAL.
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:UNCLASSIFIED WELDING FUMES=5MG/M3 PEL
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:MECHANICAL INJURY ONLY. SKIN CONTACT:MECHANICAL INJURY ONLY. MOLTEN MATERIAL MAY BURN SKIN. INGESTION:INGESTION IS UNLIKELY DUE TO PHYSICAL STATE. HOWEVER, INGESTION OF LARGE AMOUNTS OF DUST COULD CAUSE SERIOUS INJURY, EVEN DEATH. INHALATION:DUST MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT.

Explanation of Carcinogenicity:THE PRODUCT CONTAINS NO INGREDIENT AT 0.1% OR GREATER THAT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:THE ACUTE ORAL TOXICITY OF MAGNESIUM IS CONSIDERED MODERATE.

Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY MFR.

=====
===== First Aid Measures =====

First Aid:EYE:IRRIGATE IMMEDIATELY WITH WATER FOR AT LEAST 5 MINUTES. SKIN:WASH OFF DUST IN FLOWING WATER OR SHOWER. INGESTION:INDUCE VOMITING IF LARGE AMOUNTS OF DUST ARE INGESTED. CONSULT MEDICAL PERSONNEL. I NHALATION:REMOVE TO FRESH AIR IF DUST IN HALATION EFFECTS OCCUR. CONSULT A PHYSICIAN. NO SPECIFIC ANTIDOTE FOR DUST INHALATION. SUPPORTIVE CARE. PHYSICIAN:USE JUDGEMENT AND TREAT PER PATIENT REACTIONS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE.
Extinguishing Media:SMOTHER BURNING MAGNESIUM BY COVERING WITH AN EXTINGUISHING POWDER APPROVED FOR USE ON MAGNESIUM FIRES SUCH AS MET-L-X.
Fire Fighting Procedures:WEAR POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Un
usual Fire/Explosion Hazard:WHEN HEATED IN AIR TO A TEMPERATURE NEAR ITS MELTING POINT, MAGNESIUM ALLOYS IGNITE & BURN WITH A WHITE FLAME.USE OF WATER WILL PRODUCE HYDROGEN GAS & EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CLEAN OFF AND USE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE PRODUCT IN DRY LOCATION. WET, MOIST OR HIGH HUMIDITY STORAGE CONDITIONS WILL

LEAD TO CORROSION OF

THE PRODUCT. STORE AWAY FROM OTHER COMBUSTIBLE

Other Precautions:PRACTICE REASONABLE CARE IN HANDLING MAGNESIUM AND
MAGNESIUM ALLOY PRODUCTS FORMS TO AVOID DAMAGE AND/OR PERSONAL
INJURY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATORY PROTECTION SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT FOR MOST
CONDITIONS. LOCAL EXHAUST MAY NE NECESSARY FOR SOME OPERATIONS.

Protecti

ve Gloves:HMIS: WELDERS GLOVES

Eye Protection:SAFETY GLASSES(NORMAL) OR WELDING LENSES

Other Protective Equipment:USE EQUIPMENT APPROPRIATE FOR WELDING
OPERATION. OTHER OPERATIONS USE NORMAL WORK CLOTHING.

Work Hygienic Practices:MFR: ? HMIS:USE GOOD INDUSTRIAL HYGIENE
PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING
OR DRINKING.

Supplemental Safety and Health

KEY2:KT SEE NFPA BULLETIN NFPA 48.

=====
===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Melt/Freeze Pt:M.P/F.P Text:830F,443C

Spec Gravity:1.82

Appearance and Odor:SILVER SOLID. NO ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACID, WATER. - REACTS TO RELEASE HYDROGEN: AN EXPLOSIVE GAS.

Stability Condition to Avoid:STABLE UNDER NORMAL HANDLING CONDITIONS.

Hazardous Decomposition Products:NONE UNDER NORMAL USE OR STORAGE.

Conditions to Avoid Polymerization:WILL NOT OCCUR

=====

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.