

CHRYSLER CORPORATION -- MOPAR AUTOMATIC TRANSMISSION FLUID -- 9150-00-843-1636  
===== Product Identification =====

Product ID:MOPAR AUTOMATIC TRANSMISSION FLUID

MSDS Date:06/28/1985

FSC:9150

NIIN:00-843-1636

MSDS Number: BKHRX

=== Responsible Party ===

Company Name:CHRYSLER CORPORATION

Address:26311 LAWRENCE AVE.

City:CENTER LINE

State:MI

ZIP:48015-9960

Info Phone Num:(313) 956-5478 OR 956-5557

Em

ergency Phone Num:(313) 956-5478 OR 956-5557

CAGE:51926

=== Contractor Identification ===

Company Name:CHRYSLER CORPORATION

Address:26311 LAWRENCE AVE.

Box:1718

City:CENTER LINE

State:MI

ZIP:48015-9960

Phone:(313) 956-5478 OR 956-5557

CAGE:51926

===== Composition/Information on Ingredients =====

Ingred Name:PARAFFINIC PROCESS OIL

OSHA PEL:5 MG/CUM

ACGIH TLV:5 MG/CUM

Ingred Name:DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFIN

===== Hazards Identifica  
tion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION, DEFATTING, & DRYING.

EYE: IRRITATION & TEARING. INHALATION: HEADACHE, DIZZINESS, &

IRRITATION OF UPPER RESPIRATORY TRACT. INGESTION: HARMFUL, NAUSEA,

VOMITING, DIARRHEA, & ABDOMINAL CRAMPS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: IRRITATION, DEFATTING, & DRYING. EYE:

IRRITATION & TEARING. INHALATION: HEADACHE, DIZZINESS, & IRRITATION OF UPPER RESPIRATORY TRACT. INGESTION: HARMFUL, NAUSEA, VOMITING, DIARRHEA, & ABDOMINAL CRAMPS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: INDUCE VOMITING. BY TOUCHING BACK OF THROAT W/FINGER. GIVE LARGE QUANTITIES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:365F  
Extinguishing Media:DRY CHEMICAL B, FOAM, CO2, & WATER FOG.  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/CLEAN DRY SAND OR DIATOMACIOUS EARTH. SHOVEL INTO STORAGE CONTAINERS. ELIMINATE ALL IGNITION SOURCES (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC OR FRICTIONAL SPARKS).

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT, SPARK, OR OPEN FLAME. STORE AT TEMPERATURE 600F  
Vapor Pres:0  
Spec Gravity:0.870  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:CLEAR RED VISCOUS LIQUID W/SLIGHT ODOR.  
Percent Volatiles by Volume:0%

===== Stability and Reactivity Data =====

Stabilit

y Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: SPARKS, OPEN FLAME, HIGH TEMPERATURE,  
IGNITION SOURCES, HOT SURFACES, ELECTRICAL, STATIC, FRICTIONAL  
SPARKS, TEMPS >120F

Hazardous Decomposition Products: CO<sub>2</sub>, WATER, & CO.

===== Disposal Considerations =====

Waste Disposal Methods: CONTROLLED INCINERATION OR DISPOSE OF IN A  
CHEMICAL LANDFILL. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &  
FEDERAL REGULATIONS. DON'T  
FLUSH INTO SEWER SYSTEM. COMBUSTIBLE  
LIQUID.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.