View NSN Online: https://aerobasegroup.com/nsn/8010-00-847-4968

FARWEST PAINT MANUFACTURING CO. -- OLIVE DRAB LACQUER -- 8010-00-847-4968

Product ID:OLIVE DRAB LACQUER MSDS Date:02/10/1989 FSC:8010 NIIN:00-847-4968 MSDS Number: BKPJX === Responsible Party === Company Name: FARWEST PAINT MANUFACTURING CO. Address:4522 S. 133RD ST. City:TUKWILA State:WA ZIP:98168 Country:US Info Phone Num:206-244-8844 **Emergency Phone Num:206-94** 1-1619 CAGE:2F266 === Contractor Identification === Company Name: FARWEST PAINT MANUFACTURING CO Address:4522 S 133RD ST City:TUKWILA State:WA ZIP:98168 Country:US Phone:206-244-8844 CAGE:2F266 Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic: EYES: CAN CAUSE SE VERE IRRITATION. REDNESS, TEARING, BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS. BREATHING: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS & * Effects of Overexposure:*EVEN ASPHYXIATION. SWALLOWING: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CA

USE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

First Aid:SKIN: THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER. REMOVE CONTAM CLOTHING & LAUNDER BEFORE REUSE. EYES: FLUSH W/LARGE AMT WATER, LIFTING UPPER/LOWER LIDS OCCASIONALLY. GET MEDICAL AID. SWALLOW: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET & GET MEDICAL AID. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING HA S STOPPED, GIVE CPR. KEEP

QUIET & GET MEDICAL AID.

Flash Point Method:TCC Flash Point:41.0F,5.0C Lower Limits:.90 Extinguishing Media:FOAM, CO2, DRY CHEMICAL AND WATER FOG. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:NEVER USE NEAR OR AROUND WELDERS OR

CUTTING TORCHES. DRUM (EVEN EMP

TY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

Spill Release Procedures:SMALL: ABSORB W/ABSORB MAT'L & TRANSFER TO HOOD. LG: REMOVE IGNIT SOURCES. EXCLUDE PERSONS W/O PROTECT EQUIP FROM SPILL AREA UNTIL CLEAN-UP COMPLETED. STOP SPILL AT SOURCE, DIKE AREA, PUMP LIQ TO SALV AGE TANK. TAKE UP REMAINING LIQ W/ABSORB MAT'L.**

Neutralizing Agent:**PREVENT RUNOFF TO SEWERS,STREAMS,OTHER WATER

BODIES.NOTIFY PROPER AUTHORITIES.

 Handling and Storage Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID AND/OR SOLID).
Other Precautions: ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

Respiratory Protection: IF TLV IS EXCEEDED, NIOSH/MSHA JOINTL

Y APPR'D AIR SUPPLIED RSPRTR IS ADVISED IN ABSENCE OF PROPER ENVIRON CONTROL. OSHA REGS ALSO PERMIT OTHER NIOSH/MSHA RSPRTRS UNDER SPECIFIED CONDITIONS. IMPLEMENT ENGINEER/ADMIN CONTROLS TO REDUCE EXPOS. Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves:NITRILE RUBBER. Eye Protection:CHEM SPLASH GOGGLES OR SAFETY GLASSES. Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices: KEEP WORK AREA CLEAN & FREE FROM LEAKS/SPILLS. ALWAYS WASH HANDS THOROUGHLY W/SOAP & WATER BEFORE HANDLING FOOD & DRINK.

Supplemental Safety and Health

Boiling Pt:B.P. Text:167F,75C Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:NIL Appearance and Odor:OLIVE, VISCOUS LIQUID WITH MILD, ALCOHOL KETONE O DOR. Percent Volatiles by Volume: