

CHEM-PRO MANUFACTURING CO., INC. -- AGE-MASTER I RUBBER PROTECTANT --
8030-01-282-5626

===== Product Identification =====

Product ID:AGE-MASTER I RUBBER PROTECTANT

MSDS Date:07/30/1990

FSC:8030

NIIN:01-282-5626

MSDS Number: BLJPW

=== Responsible Party ===

Company Name:CHEM-PRO MANUFACTURING CO., INC.

Address:9215 HILLVIEW DR.

Box:213

City:CLARENCE

State:NY

ZIP:14031

Country:US

Info Phone Num:716-74

1-2079

Emergency Phone Num:716-741-2079

CAGE:NO362

=== Contractor Identification ===

Company Name:CHEM-PRO MANUFACTURING CO., INC.

Address:9215 HILLVIEW DR.

Box:213

City:CLARENCE

State:NY

ZIP:14031

Country:US

Phone:716-741-2079

CAGE:NO362

Company Name:U.S. DEPARTMENT OF LABOR

Address:9215 HILLVIEW DR. CLARENCE, NEW YORK 14031

Box:213

City:CLARENCE

State:NY

ZIP:14031

Country:US

Phone:716-741-2079

CAGE:62692

===== Composition/Information on Ingredients =====

Ingred Name:STODDAR

D SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION:NAUSEA, VOMITING, DIARRHEA,
GASTROINTESTINAL IRRITATION. EYES:CAN CAUSE SEVERE IRRITATION,
REDNESS, TEARING AND BLURRED VISION. SKIN :PROLONGED OR REPEATED
CONTACT CAN CAUSE MODERATE IRRITATION, DERMATITIS
IN CERTAIN
INDIVIDUALS.INHALATION:RESPIRATORY IRRITATION, DIZZINESS, NAUSEA,
HEADACHE, FATIGUE.
Explanation of Carcinogenicity:NOT LISTED AS POTENTIAL CARCINOGEN IN
OSHA, EPA, RCRA, NTP OR IARC.
Effects of Overexposure:HEADACHE, DIFFICULTY OF BREATHING, NAUSEA,
FATIGUE, NOSE AND THROAT IRRITATION, DIZZINESS.
Medical Cond Aggravated by Exposure:NOT ESTABLISHED FOR THIS PRODUCT.

===== First Aid Measures =====

First Aid:REMOVE PERSON TO FRESH
AIR. DO NOT INDUCE VOMITING. KEEP
PERSON WARM. REMOVE PRODUCT FROM SKIN WITH WATERLESS SOAP, WIPE OFF
CLEAN, THEN FOLLOW WITH WARM WATER AND REGULAR SOAP.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:143F,62C
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR SCBA WHEN FIGHTING FIRES. VAPORS ARE
HEAVIER THAN AIR & MAY BE MOVED BY VENTILATION & IGNITED BY
HEAT,PILOT LIGHTS,
PARKS OR FLAMES.
Unusual Fire/Explosion Hazard:LIQUID MAY DECOMPOSE TO POISONOUS GASSES
OF CO, CO2, NOX AND SMOKE.

===== Accidental Release Measures =====

Spill Release Procedures:PROCEED FOR HYDROCARBON SPILL APPLY.OIL
ABSORB MAT'L TO CLEAN SPILL.REMOVE SOURCES OF IGNIT.WORK FROM
UP-WIND SIDE OF SPILL AREA.TRANSFER WET ABSORB INTO CONTAINER FOR
DISPOSAL.STOP FLOW OF LIQUID INTO WATERWAY/SEWER.USE FLOATING
ABSORB TO REMOVE

=====

==== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT,SPARKS & OPEN FLAMES.STORE TIGHTLY CLOSED IN A WELL VENTED AREA.FOLLOW ESTABLISHED PLANT SAFETY REGS/PROCEEDS FOR HANDLING COMBUSTIBLES.
Other Precautions:DO NOT USE NEAR WELDING EQUIPMENT, FLAMES AND SPARKS. USE ADEQUATE VENTILATION. IF ADEQUATE VENTILATION IS NOT AVAILABLE, PROVIDE FANS OR AIR SUPPLYING EQUIPMENT.

==== Exposure Controls/Personal Protection =====

=

Respiratory Protection:ORGANIC VAPOR RESPIRATOR APPROVAL TC-23C-107 OR EQUIVALENT. NOTE:TYPE OF PROTECTIVE EQUIPMENT IS RELATED TO THE CONDITIONS OF USE AND IS THE RESPONSIBILITY OF THE USER.

Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED FOR CONFINED AREAS.

Protective Gloves:NITRILE RUBBER - HEAVY DUTY.

Eye Protection:CHEMICAL WORKER'S GOGGLES OF FACESHIELD.

Other Protective Equipment:COVERALLS OR APRON.REMOVE STAINS FROM CLOTHING/STAINED SURFACES

USING CLEANING SOLVENT.FOLLOW W/DILUTED CLOROX TO REMOVE

Work Hygienic Practices:WASH HANDS BEFORE EATING & AFTER WORK.USE WATERLESS SOAP & WIPE OFF HANDS.FOLLOW W/REGULAR SOAP/WATER.DISPOSE SOIL CLOTH

Supplemental Safety and Health

==== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:400F,204C

Vapor Pres:2.6

Vapor Density:5.4

Spec Gravity:0.795

Evaporation Rate & Reference:SLOWER(BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE/NIL

App

pearance and Odor:DARK REDDISH-BROWN

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:THERMAL DECOMPOSITION

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS: CO, CO2, NOX, VARIOUS HYDROCARBONS.

==== Disposal Considerations =====

Waste Disposal Methods:INCINERATE AS SOLID WASTE AT APPROVED STATE WASTE DISPOSAL PLANTS. THE SAME FOR

EMPTY DRUMS. REMOVE LIQUID FROM
DRUMS WITH ABSORBENT, THEN DISPOSE AS SOLID WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
as
sume responsibility for the suitability of this information to their
particular situation.