

DIAL CORP THE -- EA 9396 PART B -- 8040-00-209-1286

===== Product Identification =====

Product ID:EA 9396 PART B
MSDS Date:09/29/1989
FSC:8040
NIIN:00-209-1286
Kit Part:Y
MSDS Number: BLJSH
=== Responsible Party ===
Company Name:DIAL CORP THE
Address:1865 DIAL TOWER
Box:312
City:PHOENIX
State:AZ
ZIP:85077-1865
Country:US
Info Phone Num:602-991-3000
Emergency Phone Num:602-991-3000
Preparer's Name
:SUZANNE FRANZ
CAGE:0EK45

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address:2850 WILLOW PASS ROAD
Box:312
City:BAY POINT
State:CA
ZIP:94565-3299
Country:US
Phone:202-483-7616
CAGE:33564
Company Name:DIAL CORP THE
Address:111 W CLARENDON AVE
Box:3223
City:PHOENIX
State:AZ
ZIP:85077
Country:US
Phone:602-991-3000
CAGE:0EK45

===== Composition/Information on Ingredients =====

Ingred Name:ALKYLAMINES
Fraction by Wt: 149C
Extinguish

ing Media: DRY CHEMICAL, HALON FIRE EXTINGUISHER, WATER SPRAY,
FOAM OR FOG.

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard: DENSE SMOKE AND TOXIC GASES MAY BE
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY
GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP
REMAINING RESIDUE WITH SOLV
ENTS, OBSERVING SOLVENT FLAMMABILITY
CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP COOL IN ACCORDANCE WITH LABEL
INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG. F) FOR 12 MONTHS.
FOLLOW RECOMMENDED CURING SCHEDULE.

Other Precautions: FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE
HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASES.

===== Exposure Controls/Personal Protection =====

Respirator

y Protection: NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation: LOCAL EXHAUST RECOMMENDED.

Protective Gloves: IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection: SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practices: WASH AFTER HANDLING. DO NOT USE UNTIL THE MSDS
HAS BEEN READ AND UNDERSTOOD.

Supplemental Safety and Health

KEY1: C2. CAUSES IRRITATION TO SKIN AND EYES. CONTAINS
TETRAETHYLENEPENTAMINE. AVOID CONTACT. VAPORS MAY BE
IRRITATING.

AVOID BREATHING VAPORS. KEEP CONTAINER CLOSED. USE ONLY WITH GOOD
VENTILATION. DO NOT CUT OR WELD CONTAINER.

===== Physical/Chemical Properties =====

HCC: B2

Boiling Pt: B.P. Text: 644F, 340C

Vapor Pres: 1 LB. DO NOT HEAT MIXED ADHESIVE UNLESS CURING SURFACES TO
BE BONDED.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO
LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.