

COATES REPROGRAPHICS INC -- BIMODE TONER OH PREMIX -- 6850-01-167-5992

=====
Product Identification
=====

Product ID:BIMODE TONER OH PREMIX

MSDS Date:03/01/1989

FSC:6850

NIIN:01-167-5992

MSDS Number: BLPHF

=== Responsible Party ===

Company Name:COATES REPROGRAPHICS INC

Address:COUNTRY CLUB RD

Box:160

City:DALLAS

State:PA

ZIP:18612-9171

Country:US

Info Phone Num:717-675-1131

Emergency Phone Num:

717-675-1131

CAGE:3S299

=== Contractor Identification ===

Company Name:COATES REPROGRAPHICS INC

Address:COUNTRY CLUB RD

Box:City:DALLAS

State:PA

ZIP:18612-9171

Country:US

Phone:717-675-1131

CAGE:3S299

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED HEAVY NAPHTHA

CAS:64742-48-9

Fraction by Wt: >99%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingesti

on: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure: INHALATION OF HIGH VAPOR CONCENTRATIONS MAY HAVE RESULTS RANGING FROM DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS. PROLONGED OR REPEATED LIQUID CONTACT WITH SKIN CAN DRY AND DEFAT THE SKIN POSSIBLY LEADING TO IRRITATION AND DERMATITIS.

Medical Cond Aggravated by Exposure: NO INFORMATION AVAILABLE.

=====
First Aid Measures

First Aid: INHALATION: REMOVE FROM EXPOSURE IMMEDIATELY; CALL A PHYSICIAN. ADMINISTER OXYGEN OR CPR IF NECESSARY. SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP AND WARM WATER. EYES: FLUSH WITH CLEAR WATER FOR 15 MIN. OR UNTIL IRRITATION SUBSIDES. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

=====
Fire Fighting Measures

Flash Point Method: TCC

Flash Point: 104F, 40C

Lower Limits: 0.

8

Upper Limits: 7.0

Extinguishing Media: FOAM, DRY CHEMICAL, WATER SPRAY OR MIST, OR CARBON DIOXIDE.

Fire Fighting Procedures: USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: AVOID BREATHING VAPOR OR FUMES. THIS PRODUCT IS COMBUSTIBLE.

=====
Accidental Release Measures

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP PEOPLE AWAY. RECOVER FREE LIQUID. ADD AB

SORBENT TO SPILL AREA. AVOID BREATHING

VAPORS. VENTILATE CONFINED SPACES. KEEP OUT OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING.

Neutralizing Agent: NONE

=====
Handling and Storage

Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS. ADEQUATE VENTILATION IS REQUIRED.

Other Precautions: AVOID BREATHING VAPORS. AVOID PROLONGED OR REPEATED CONTACT

CT WITH SKIN. REMOVE CONTAMINATED CLOTHING, LAUNDER BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED.

Ventilation:USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:CHEMICAL-RESISTANT APRON OR CLOTHING IF NEEDED.

Work Hygienic P

ractices:WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER CONTACT WITH THIS PRODUCT.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres: