

TITAN ADHESIVE CO, INC -- 6000 MODIFIED LIQUID ANIMAL WATER BASED -- 8040-00-262-9068
===== Product Identification =====

Product ID:6000 MODIFIED LIQUID ANIMAL WATER BASED

MSDS Date:06/12/1991

FSC:8040

NIIN:00-262-9068

MSDS Number: BLSRN

=== Responsible Party ===

Company Name:TITAN ADHESIVE CO, INC

Address:590 BELLEVILLE TURNPIKE

City:KEARNY

State:NJ

ZIP:07032

Country:US

Info Phone Num:201-997-12

81

Emergency Phone Num:201-997-1281

Preparer's Name:STEVE BASCH

CAGE:TITAN

=== Contractor Identification ===

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

Company Name:TITAN ADHESIVE CO, INC

Address:590 BELLEVILLE TURNPIKE

City:KEARNY

State:NJ

ZIP:07032

Phone:201-997-1281

CAGE:TITAN

===== Composition/Information on Ingredients =====

Ingred Name:PROPRIETARY (NJEIN 36288800-5164P)

Other REC

Limits:NONE SPECIFIED

Ingred Name:PROPRIETARY (NJEIN 36288800-5107P)

Other REC Limits:NONE SPECIFIED

Ingred Name:THIOUREA (SARA III)

CAS:62-56-6

RTECS #:YU2800000

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION:MAY CAUSE SLIGHT IRRITATION
TO NAS
AL TRACT. MAY CAUSE DEPRESSION OF BONE MARROW W/ANEMIA,
LEUKOPENIA AND AGRANYLOCYTOSIS. INGESTION: NOT PROBABLE OR LIKELY.
EYES MAY CAUSE SLIGHT IRRITATION . SKIN: MAY CAUSE SLIGHT
IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYES: IRRIGATE IMMEDIATELY WITH WATER FOR AT LEAST 15
MINUTES. SKIN: WASH OFF IN FLOWING WATER. WASH CONTAMINATED
CLOTHING BEFORE REUSE. INGESTION: DRINK WATER AND/OR MILK. DO
INDUCE VOMITING. CALL A P
HYSICIAN AND/OR TRANSPORT TO
EMERGENCYFACILITY IF REQUIRED. INHALATION: REMOVE TO FRESH AIR AND
IF SYMPTOMS OF OVER EXPOSURE DEVELOP SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:LIQUID WILL NOT BURN. DRY FILM CAN BURN. EXTINGUISH
WITH WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WHEN
EXTINGUISHING FIRE.
Unusual Fire/Explosion Hazard

:MATERIAL MAY SPLATTER OVER 212 F.

===== Accidental Release Measures =====

Spill Release Procedures:SHOVEL OR CLEAN UP SPILLED MATERIAL WITH SUITABLE ABSORBENT AND PLACE IN AN APPROVED CONTAINER. LET FILM DRY AND THEN SCRAPE UP.

===== Handling and Storage =====

Handling and Storage Precautions:FOR BEST RESULTS OF PRODUCT STORE AT TEMPERATURES BETWEEN 50 AND 90 F.

Other Precautions:KEEP FROM FREEZING.

===== E
xposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventilation:LOCAL EXHAUST WITH MECHANICAL ASSISTANCE IF REQUIRED.

Protective Gloves:WATER PROOF OR IMPERVIOUS GLOVES.

Eye Protection:SPLASH-PROOF EYE PROTECTION.

Other Protective Equipment:NO SPECIAL CLOTHING REQUIRED.

Work Hygienic Practices:GOOD HOUSEKEEPING PRACTICES ARE IMPORTANT. WASH THOROUGHLY AFTER USING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

=====

HCC:T4

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:18 @ 20 C

Vapor Density: