

NEVAMAR CORP -- NEVAMAR LAMINATED PLASTIC -- 9330-01-021-2224

===== Product Identification =====

Product ID:NEVAMAR LAMINATED PLASTIC

MSDS Date:01/01/1988

FSC:9330

NIIN:01-021-2224

MSDS Number: BMTQD

=== Responsible Party ===

Company Name:NEVAMAR CORP

Address:8339 TELEGRAPH RD

City:ODENTON

State:MD

ZIP:21113-1322

Country:US

Info Phone Num:301-569-5000

Emergency Phone Num:301-569-5000

Preparer's

Name:PAUL R. GARTELMAN

CAGE:92570

=== Contractor Identification ===

Company Name:NEVAMAR CORP

Address:8339 TELEGRAPH RD

Box:City:ODENTON

State:MD

ZIP:21113-1322

Country:US

Phone:301-569-5000

CAGE:92570

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENT

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of

Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION-LAMINATE DUST IS SIMILIAR TO WOOD DUST WHICH HAS BEEN CLASSIFIED AS A NUISANCE DUST. EYE-IRRITATION MAY ARISE FROM EXCESSIVE NUISANCE DUST.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
Effects of Overexposure:MAY CAUSE EYE IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MA NUFACTURER.

===== First Aid Measures =====

First Aid:EYE CONTACT: IF EXPOSURE TO NUISANCE DUST OCCURS, FLUSH EYES THOROUGHLY FOR AT LEAST 15 MINUTES. CONTACT PHYSICIAN IF IRRITATION PERSISTS.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER SPRAY, WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL TO EXTINGUISH FIRES.
Fire Fighting Procedures:USE WATER SPRAY TO COOL EXPOSED SURFACES TO FIRE AND TO PROTECT PERSONNEL.
Unusual Fire/Explosion Hazard:CHARACTERISTICS ARE SIMILIAR TO WOOD AND PAPER PRODUCTS.

===== Handling and Storage =====

Handling and Storage Precautions:CHARACTERISTICS ARE SIMILIAR TO WOOD AND PAPER PRODUCTS.
Other Precautions:FOLLOW SAFE WORK PRACTICES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED DUST RESPIRATOR IF DUST IS PR
OBLEM WHILE SAWING.
Ventilation:LOCAL AND MECHANICAL(GENERAL) EXHAUST TO PROVIDE ADEQUATE VENTILATION.
Protective Gloves:CLOTH GLOVES RECOMMENDED
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:NONE
Work Hygienic Practices:FOLLOW SAFE WORKING PRACTICES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:NONE
Spec Gravity:1.2 @70F
Solubility in Water:SLIGHT
Appearance and Odor:SOLID SHEETS, SLI

GHT ODOR.

Percent Volatiles by Volume:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ALL DUST AND CHIPS VIA SANITARY
LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by e

lements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.