

FISKE BROTHERS REFINING CO -- 130A 130AA -- 9150-00-857-9079

===== Product Identification =====

Product ID:130A 130AA

MSDS Date:05/01/1987

FSC:9150

NIIN:00-857-9079

MSDS Number: BMWVK

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFININ

G CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingest

ion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN; PROLONGED CONTACT MAY CAUSE REDDENING, IRRITATION. EYES; IRRITATION. INGESTION; MINUTE AMOUNTS ASPIRATED INTO THE LUNG MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE KNOWN

=====
===== First Aid Measures =====

First Aid:EYES; FLUSH WITH WATER FOR 15MINUTES. IF IRRITATION PERSIS

T

CONT A DOCTOR. SKIN;REMOVE ANY CONTAMINATED CLOTH AND WASH WITH SOAP AND WATER. IF INJECTED BY HIGH PRESSURE UNDER THE SKIN CONTACT A PHYSCI AN IMMEDIATELY REGARDLESS.INHALATION;IFOVERCOME FROM VAPOR OF A HOT PRODUCT REMOVE TO FRESH AIR IMMEDIATELY.'

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Lower Limits:0.9

Upper Limits:7

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG)

Fir

e Fighting Procedures:WEAR SCBA FOR CONFINED SPACES, COOL EXPOSED CONTAINERS WITH WATER

Unusual Fire/Explosion Hazard:NA

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE WASH REMAINDER WITH APPROPRIATE SOLVENT OR ADD ABSORBENT.KEEP PRODUCT OUT OF WATERWAYS AND SEWERS.

Neutralizing Agent:NA

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT

IN

USE, DO NOT HANDLE OR STORE NEAR HEAT, SPARKS OR FLAMES. OR STRONG OXIDANTS.

Other Precautions: REMOVE OIL SOAK CLOTHING AND LAUNDER BEFORE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NORMALLY NOT REQUIRED
Ventilation: USE TO CAPTURE FUMES AND VAPORS
Protective Gloves: OIL RESISTANT IF NEEDED
Eye Protection: GOGGLES IF NEEDED
Other Protective Equipment: OIL RESISTANT APRON IF NEEDED
Work Hygienic Practices: CLEANSE SKIN THOROUGHLY AFTER USE
Supplemental Safety and Health
NA

=====
===== Physical/Chemical Properties =====

HCC: V6
Boiling Pt: B.P. Text: >550F, >288C
Vapor Pres: < 0.01
Vapor Density: >5
Spec Gravity: 0.97-0.983
Evaporation Rate & Reference: < 0.01
Solubility in Water: NELIGIBLE
Appearance and Odor: SMOOTH TAN GREASE WITH MINERAL OIL ODOR

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDANTS
Stability Condition to Avoid: NA

Hazardous Decomposition Products: SO₂, CARBON MONOXIDE

=====
===== Disposal Considerations =====

Waste Disposal Methods: AT A APPROVED FACILITY IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be ac

curate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.