

GENERAL MOTORS CORP, GENERAL MOTORS BUILDING -- REFRIGERANT 12 -- 6830-00-935-9895
===== Product Identification =====

Product ID:REFRIGERANT 12

MSDS Date:10/26/1987

FSC:6830

NIIN:00-935-9895

MSDS Number: BMXJR

=== Responsible Party ===

Company Name:GENERAL MOTORS CORP, GENERAL MOTORS BUILDING

Address:3044 GRAND BLVD W

City:DETROIT

State:MI

ZIP:48202-3091

Country:US

Emergency Phone Num:301-258-1

535

CAGE:24617

=== Contractor Identification ===

Company Name:GENERAL MOTORS CORP

Address:GENERAL MOTORS BUILDING 3044 GRAND BLVDW

Box:City:DETROIT

State:MI

ZIP:48202-3091

Country:US

Phone:301-258-1535

CAGE:24617

===== Composition/Information on Ingredients =====

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:DICHLORODIFLUOROMETHANE IS NOT LISTED AS
A CARCINOGEN BY IARC, NTP OR OSHA.
Effects of Overexposure:CONTACT WITH OPEN FLAMES MAY CAUSE
LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND
FROSTBITE.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION &
OXYGEN IF BREATHING STOPS. GET MEDICAL ATTENTION, IF NEEDED, FOR
ALL OVEREXPOSURES.

=====
===== Fire Fighting Measures =====

Unusual Fire/Explosion Hazard:ON HEATING TO DECOMPOSITION, MAY PRODUCE
HALOGEN ACIDS & PHOSGENE. PRESSURIZED PR
ODUCT - NONFLAMMABLE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA, ESPECIALLY LOW PLACES WHERE
VAPORS MIGHT COLLECT. CONTACT WITH HEAT OR HIGH FLAMES SHOULD BE
AVOIDED.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN WELL-VENTILATED DRY AREA
(BELOW 125F). CONTACT WITH FLAME OR HIGH HEAT SHOULD BE AVOIDED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A SELF-CONTAINED BREATHING APPARATUS IF
NEEDED.
Ventilation:PROVIDE LOCAL EXHAUST TO REDUCE CONCENTRATION.
Protective Gloves:RUBBER GLOVES.
Eye Protection:MONOGOGGLES
Work Hygienic Practices:DO NOT SMOKE IN AREA WHILE PRODUCT IS IN USE.
Supplemental Safety and Health
NONE

=====
===== Physical/Chemical Properties =====

HCC:G3
Boiling Pt:B.P. Text:-22F,-30C
Melt/Freeze Pt:M.P/F.P Text:-158F,-106C
Vapor Pres:20
Spec Gravity:1

.326

Solubility in Water:0

Appearance and Odor:COLORLESS, LIQUIDIFIED COMPRESSED GAS. FAINT ETERAL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NOT PROVIDED

Stability Condition to Avoid:NOT PROVIDED

Hazardous Decomposition Products:NOT PROVIDED

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ALL WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

D

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation